

1125 SERIES *HAND CRANK & MOTOR DRIVEN HOSE REELS*



1125-E Series with optional 4-way roller bracket

1125 Series

COXREELS® 1125 Series hand crank and motorized hose reels have the features demanded by industry professionals. The industry preferred design features a sturdy one piece all welded "A" frame base, low profile outlet riser and open drum slot design provides a non-crimping, flat smooth hose wrap.

1125 SERIES MODELS - ALL REELS SUPPLIED LESS HOSE

MODEL	STANDARD CAP			OPTIONAL CAP. Reducer required			INLET SWIVEL & OUTLET RISER mm	BAR	MODEL	HP BAR	Kg.	SIZE INDEX
	I.D. mm	O.D. mm	LENGTH m	I.D. mm	O.D. mm	LENGTH m						
1125-4-100	13	22	30	10	19	43	13 F NPT	207	HP1125-4-100	345	16	1
1125-4-200	13	22	61	10	19	91	13 F NPT	207	HP1125-4-200	345	18	2
1125-4-325	13	22	99	10	19	137	13 F NPT	207	HP1125-4-325	345	22	3
1125-4-450	13	22	137	10	19	191	13 F NPT	207	HP1125-4-450	345	24	4
1125-4-500	13	22	152	10	19	213	13 F NPT	207	HP1125-4-500	345	26	5
1125-5-50	19	32	15	13	22	30	19 F NPT	207	HP1125-5-50	310	17	6
1125-5-100	19	32	30	13	22	61	19 F NPT	207	HP1125-5-100	310	19	7
1125-5-175	19	32	53	13	22	99	19 F NPT	207	HP1125-5-175	310	23	8
1125-5-200	19	32	61	13	22	137	19 F NPT	207	HP1125-5-200	310	25	9
1125-5-250	19	32	76	13	22	152	19 F NPT	207	HP1125-5-250	310	27	10
1125-6-35	25	36	11	19	32	15	25 F NPT	207	-	-	23	11
1125-6-50	25	36	15	19	32	23	25 F NPT	207	-	-	25	12
1125-6-75	25	36	23	19	32	37	25 F NPT	207	-	-	28	13
1125-6-100	25	36	30	19	32	46	25 F NPT	207	-	-	31	14

1125 SERIES :: REEL SPECIFICATIONS

SWIVEL

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Nickel plated steel swivel on 25 mm models)
- Swivel Seals: NITRILE (AFLAS on 25 mm models)
- External fluid path with electroless nickel plated steel 90° full-flow NPT swivel inlet (On high pressure HP prefix models)
- Swivel Seals: AFLAS (On high pressure HP prefix models)

DESIGN & STRUCTURE

- All welded steel "A" frame construction for superior reel structure
- Exclusive low profile outlet riser & open drum slot design for flat smooth hose wrap
- Permanently lubricated self-aligning pillow block bearings for trouble-free & smooth rotation
- Adjustable tension brake to prevent "free-wheeling" during operation
- Long-handled locking pin to secure reel from rotation during transport or storage

RETRACTION

- Reliable direct gear drive on motor driven models providing quiet & smooth retraction - **NO CHAIN**
- Solid steel direct hand crank with smooth round handle
- See Motor Options Chart

SIGNATURE FEATURES

- Professional grade heavy duty steel construction
- Durable proprietary CPC™ powder coat process
- Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- Made in the U.S.A. - Sold & Supported Worldwide

POSSIBLE FIELDS OF APPLICATION

- Industrial Plant & Ground Maintenance
- Fire Suppression
- Farming
- Construction Sites
- Landscape
- Pest & Weed Control
- Golf Course Maintenance
- Air Compressor
- Washdown
- High-Flow Watering
- Hydro Seeding
- Pressure Washing
- Agricultural Spraying
- Chemical Fluid Transfer

ACCESSORIZE YOUR REEL :: PG 50

- O-Rings & Swivels
- Roller Brackets
- Stacking Brackets
- Hoses
- Assorted Reel Accessories



MOTOR OPTIONS

When ordering, suffix the model number with selection below. NOTE: Add 5 lbs to ship weight if reel is crated

SUFFIX	TYPE	DESCRIPTION	ADD ON APRX. Kg*
A	AIR - #4 GAST	COMP. AIR MOTOR	4
AB	AIR - #6 GAST	COMP. AIR MOTOR	4
E	ELEC. - 12V DC	1/3 HP REW. REV. TYPE	6
EF	ELEC. - 24V DC	1/3 HP REW. REV. TYPE	6
EB	ELEC. - 24V DC	1/2 HP REW. REV. TYPE	12
ED	ELEC. - EXPL. PRF. - 12V DC	1/2 HP REW. REV. TYPE	12
EA	ELEC. - EXPL. PRF. - 115V	1/2 HP REW., AC REV. TYPE	12
H	HYDRAULIC	END PORTED 9/16-18 UNF REV.	3
C*	FRONT HAND CRANK	BEVEL GEARED CRANK	1

*Not available on 1" models, please refer to the 1175 series on the next page

REEL DIMENSIONS

Technical Data Sheets Available On Website

SIZE INDEX	W mm			H mm		L mm	X mm	Y mm		Ø mm	Dw mm
	CRANK	ELEC.	AIR / HYD.	CRANK	ELEC.			CRANK	ELEC.		
1	495	502	432	476	489	448	289	391	406	159	152
2	648	654	584	476	489	448	441	391	406	159	305
3	800	806	737	476	489	448	594	391	406	159	457
4	953	959	889	476	489	448	746	391	406	159	610
5	1054	1060	991	476	489	448	848	391	406	159	711
6	527	508	441	476	489	448	289	391	406	159	152
7	679	660	594	476	489	448	441	391	406	159	305
8	832	813	746	476	489	448	594	391	406	159	457
9	984	965	899	476	489	448	746	391	406	159	610
10	1086	1067	1000	476	489	448	848	391	406	159	711
11	660	606	565	470	486	448	378	391	406	210	241
12	813	759	718	470	486	448	530	391	406	210	394
13	978	924	883	470	486	448	695	391	406	210	559
14	1130	1076	1035	470	486	448	848	391	406	210	711

Overall Dimensions

Base

Drum

