

PERFORMANCE HOSE REELS P SERIES

COXREELS® P Series "Performance" spring driven hose reels have a long history of dependability and trouble free performance. Their compact space-saving size and heavy duty construction make them highly versatile and virtually indestructible. Time-tested proven components, superior design and craftsmanship have contributed to it's worldwide reputation as the most trusted hose reel.

LOW PRESSURE

Models with hose are for air or water service with a maximum temperature 65° C. Models less hose can be used for air, water or oil.
Note: Do not exceed listed hose O.D. to obtain maximum length.

HOSE							LESS HOSE		SIZE INDEX
MODEL	I.D. mm	O.D. mm	LENGTH m	BAR	Kg.	EZ-COIL MODELS	MODEL	Kg.	
P-LP-125	6	13	8	21	12	EZ-P-LP-125	P-LPL-125	11	1
P-LP-130	6	13	9	21	12	-	P-LPL-130	11	1
P-LP-135	6	13	11	21	13	EZ-P-LP-135	P-LPL-135	11	1
P-LP-140	6	13	12	21	17	-	P-LPL-140	15	3
P-LP-150	6	13	15	21	18	EZ-P-LP-150	P-LPL-150	16	3
P-LP-325	10	16	8	21	13	EZ-P-LP-325	P-LPL-325	11	2
P-LP-330	10	16	9	21	17	EZ-P-LP-330	P-LPL-330	15	3
P-LP-335	10	16	11	21	17	EZ-P-LP-335	P-LPL-335	15	3
P-LP-340	10	16	12	21	18	-	P-LPL-340	15	3
P-LP-350	10	16	15	21	20	EZ-P-LP-350	P-LPL-350	16	3
P-LP-415	13	19	5	21	19	-	P-LPL-415	17	4
P-LP-425	13	19	8	21	20	-	P-LPL-425	18	4
P-LP-430	13	19	9	21	20	EZ-P-LP-430	P-LPL-430	18	4
P-LP-450	13	19	15	21	22	EZ-P-LP-450	P-LPL-450	20	4

To order EZ-Coil® equipped models less hose, please add prefix "EZ-"

MEDIUM PRESSURE

Reels are furnished with standard one wire braid hose suitable for air, water or oil applications. Hose exceeds SAE R1 specifications. Maximum temperature 120° C. **Note: Do not exceed listed hose O.D. to obtain maximum length.**

HOSE							LESS HOSE		SIZE INDEX
MODEL	I.D. mm	O.D. mm	LENGTH m	BAR	Kg.	EZ-COIL MODELS	MODEL	Kg.	
P-MP-320	10	17	6	207	21	-	P-MPL-320	19	4
P-MP-325	10	17	8	207	22	-	P-MPL-325	19	4
P-MP-330	10	17	9	207	23	-	P-MPL-330	20	4
P-MP-335	10	17	11	207	24	-	P-MPL-335	20	4
P-MP-420	13	21	6	172	21	-	P-MPL-420	19	4
P-MP-425	13	21	8	172	22	EZ-P-MP-425	P-MPL-425	19	4
P-MP-430	13	21	9	172	23	EZ-P-MP-430	P-MPL-430	20	4

To order EZ-Coil® equipped models less hose, please add prefix "EZ-"

HIGH PRESSURE

Reels are furnished standard with S.A.E. 100R16 #1 or #2 wire braid hose suitable for grease and hydraulic oil applications. Maximum temp. 120° C. **Note: Do not exceed listed hose O.D. to obtain maximum length.**

HOSE							LESS HOSE		SIZE INDEX
MODEL	I.D. mm	O.D. mm	LENGTH m	BAR	Kg.	EZ-COIL MODELS	MODEL	APRX. LBS.	
P-HP-120	6	14	6	345	21	-	P-HPL-120	19	4
P-HP-125	6	14	8	345	22	EZ-P-HP-125	P-HPL-125	19	4
P-HP-130	6	14	9	345	23	-	P-HPL-130	20	4
P-HP-135	6	14	11	345	23	-	P-HPL-135	20	4
P-HP-320	10	17	6	276	21	-	P-HPL-320	19	4
P-HP-325	10	17	8	276	22	EZ-P-HP-325	P-HPL-325	19	4
P-HP-330	10	17	9	276	23	-	P-HPL-330	20	4


To order EZ-Coil® equipped models less hose, please add prefix "EZ-"

REEL DIMENSIONS

Technical Data Sheets Available On Website

SIZE INDEX	W mm	H mm	L mm	X mm	Y mm	M mm	N mm
1	149	378	343	127	152	76	127
2	165	378	343	127	152	76	127
3	171	473	435	152	152	102	127
4	178	473	435	152	152	102	127

Overall Dimensions Base Mounting Pattern



P SERIES :: REEL SPECIFICATIONS

SWIVEL

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Zinc plated steel swivel on HP models)
- Swivel Seals: NITRILE

DESIGN & STRUCTURE

- Sturdy single pedestal reel with space saving design facilitates workplace organization
- Guide arm adjusts to wall, floor, vehicle & overhead positions
- Solid one piece, heavy gauge 6 mm steel base & support post for maximum stability
- 25 mm solid steel axle & lubricated precision bearings for smooth rotation

RETRACTION

- Controlled retraction speed up to 80% slower on EZ-COIL models :: See page 7 for details
- Enclosed factory tuned & matched cartridge-style spring motor
- Non-corrosive stainless steel spring, pawl & zinc plated ratchet
- Multi-position lock ratchet mechanism secures hose at desired length

SIGNATURE FEATURES

- Professional grade heavy duty steel construction
- Durable proprietary CPC™ powder coat process
- Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- Made in the U.S.A. - Sold & Supported Worldwide

POSSIBLE FIELDS OF APPLICATION

- Air/Water Services
- Pneumatic Tools
- Washdown
- Lubrication
- Chemical Fluid Transfer
- General Industrial
- Manufacturing Plants & Facilities
- Maintenance, Repair & Operations
- Automotive & Fleet Service Centers

ACCESSORIZE YOUR REEL :: PG 50

- O-Rings & Swivels
- Mounting Brackets
- Hoses
- Assorted Reel Accessories

SPRING DRIVEN

