C SERIES **DUAL PURPOSE HOSE REELS - AIR/ELECTRIC**

COXREELS® C Series "Combination" spring driven air hose/electric cord reels are two reels in one compact assembly. They are perfect for applications that require pneumatic air and an electrical power feed. The single expanded mounting base creates stability and adds to the convenience of one mounting pattern. This series is also available in dual hose combinations.


FOR INDOOR USE ONLY


Coxreels electric and pneumatic hose reels operate as two independent, self-retracting 15 meter trouble-free assemblies. All models rated: 115 volts, 3* conductors, 60 hz single phase.

All models rated: 115 volts, 3° conductors, 60 nz single phase. HOSE & CORD											SIZE
MODEL	ACCESSORY	CORES / AWG	Ø (mm ²)	CORD m	AMPS.	I.D. m	0.D . m	LENGTH m	BAR	Kg	INDEX
C-L350-5016-A	Single Industrial Receptacle [†]	3 / 16 GA	1.31	15	13	10	16	15	21	43	1
C-L350-5012-A		3 / 12 GA	3.31	15	20	10	16	15	21	44	1
C-L350-5012-B	Quad "4 Plug" Industrial Receptacle [†]	3 / 12 GA	3.31	15	20	10	16	15	21	44	1
C-L350-5016-C	Fluorescent Tube Light - Shock Absorbing & Shatter Resistant [†]	3 / 16 GA	1.31	15	0.3	10	16	15	21	43	1
C-L350-5016-D	Fluorescent Angle Light with Tool Tap Plug [†]	3 / 16 GA	1.31	15	13	10	16	15	21	43	1
C-L350-5016-D2	Dual Fluorescent Angle Light with Tool Tap Plug [†]	3 / 16 GA	1.31	15	12	10	16	15	21	43	1
C-L350-5016-E	Incandescent Caged Drop Light with Tool Tap Plug [†]	3 / 16 GA	1.31	15	13	10	16	15	21	43	1
C-L350-5016-F	Duplex G.F.C.I. Metal Industrial Receptacle [†]	3 / 16 GA	1.31	15	13	10	16	15	21	43	1
C-L350-5012-F	-	3 / 12 GA	3.31	15	20	10	16	15	21	44	1
C-L350-5016-X	With Hose, With Cord, Less Accessory	3 / 16 GA	1.31	15	13	10	16	15	21	42	1
C-L350-5012-X		3 / 12 GA	3.31	15	20	10	16	15	21	43	1
C-L350L-5016L-X	Less Hose, Less Cord.	3 / 16 GA	1.31	15	25	10	16	15	21	35	1
C-L350L-5012L-X	Less Accessory	3 / 12 GA	3.31	15	25	10	16	15	21	35	1

REEL DIMENSIONS Technical Data Sheets Available On Website

SIZE INDEX	W mm	H mm	L mm	X mm	Y mm	M mm	N mm	
1	406	473	432	203	229	178	203	
Overall Dimensions				Ba	ise	Mounting Pattern		





(UL) Listed[†] :: Accessories only

- SWIVEL & LEAD CABLE
 - External fluid path with machined from solid brass 90° full-flow NPT swivel inlet
 - Swivel Seals: NITRILE
 - External CPC[™] powder coated steel components cover for simple slip ring routine maintenance

C SERIES :: REEL SPECIFICATIONS

· Include 2 m lead cable & grounding plug (except on less cord models)

DESIGN & STRUCTURE

- · Compact two reel assembly for air/electric applications, each reel operates independently
- · Guide arm adjusts to wall, floor & overhead positions
- · Single expanded, 6 mm steel mounting base for increased stability & space efficiency
- · One mounting pattern allow 1/2 the installation time required to install 2 reels at one station
- · 25 mm solid steel axle & lubricated precision bearings for smooth rotation

RETRACTION

- · Enclosed factory tuned & matched cartridge-style spring motor
- · Non corrosive stainless steel spring, pawl & zinc plated ratchet
- · Multi-position lock ratchet mechanism secures hose/cord at desired length

SIGNATURE FEATURES

- · Professional grade heavy duty steel construction
- Durable proprietary CPC[™] powder coat process
- · Rolled edges & ribbed discs provide strength & safety
- · Leading 2-year manufacturer's limited warranty
- · Made in the U.S.A. Sold & Supported Worldwide

POSSIBLE FIELDS OF APPLICATION

- Air Services
- Pneumatic Tools
- · Power Tools
- Light Source
- General Industrial

ACCESSORIZE YOUR REEL .:. PG 50

- · 0-Rings & Swivels
- Mounting Brackets
- Hoses Assorted Reel Accessories

 Manufacturing Plants & Facilities

Maintenance, Repair

Automotive & Fleet

Service Centers

& Operations

