# **PC<sup>10</sup> SERIES** COMPACT POWER CORD REELS



**PC<sup>10</sup> SERIES** :: REEL SPECIFICATIONS

Listed<sup>†</sup> :: Accessories only

- SLIP RING
  - External heavy gauge CPC™ powder coated steel
  - components cover for simple slip ring routine maintenance • Electrical current runs through a 25AMP / 600V rated
  - slip ring • Include 2 m lead cable & grounding plug (except on less
- Include 2 m lead cable cord models)
   DESIGN & STRUCTURE
  - Selection of electrical accessories
  - Compact & lightweight spring driven cord reel save space & facilitate workplace organization
  - CoxComposite  $^{\rm TM}$  grommet with continuous radius design that does not pinch or catch the cord during operation
  - Solid one piece, 2 mm steel base & support post for maximum stability
  - $\bullet$  13 mm solid steel axle & lubricated precision bearings for smooth rotation

#### RETRACTION

- Enclosed factory tuned & matched cartridge-style spring motor
- Non-corrosive CoxComposite™ ratchet hub with self lubricating bronze bearings secures cord at desired length

### SIGNATURE FEATURES

- · Professional grade heavy duty steel construction
- Durable proprietary CPC<sup>™</sup> powder coat process
- Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- Made in the U.S.A. Sold & Supported Worldwide

## **POSSIBLE FIELDS OF APPLICATION**

- Power Tools
- Light Source
- General Industrial
- Bench Mount
- Manufacturing Plants
- & Facilities

<ul> <li>Workshops</li> </ul>
Automotive & Fleet
Service Centers

 Service / Mechanic / Utility Vehicles

	GUKU								SIZE
	MODEL	ACCESSORY	CORES / AWG	<b>Ø</b> (mm²)	CORD m	VOLTS	AMPS	Kg.	INDEX
	PC10-3016-A	Single Industrial Receptacle <sup>†</sup>	3 / 16 GA	1.31	9	115	13	6	1
	PC10-3012-A		3 / 12 GA	3.31	9	115	20	8	1
	PC10-3012-B	Quad "4 Plug" Industrial Receptacle <sup>†</sup>	3 / 12 GA	3.31	9	115	20	8	1
y	PC10-3016-C	Fluorescent Tube Light - Shock Absorbing & Shatter Resistant <sup>†</sup>	3 / 16 GA	1.31	9	115	0.3	7	1
	PC10-3016-D	Fluorescent Angle Light with Tool Tap Plug <sup>†</sup>	3 / 16 GA	1.31	9	115	13	7	1
	PC10-3016-E	Incandescent Caged Drop Light with Tool Tap Plug <sup>+</sup>	3 / 16 GA	1.31	9	115	13	6	1
	PC10-3016-F	Duplex G.F.C.I. Metal Industrial Receptacle <sup>†</sup>	3 / 16 GA	1.31	9	115	13	7	1
	PC10-3012-F	-	3 / 12 GA	3.31	9	115	20	9	1
	PC10-3016-X	With Hose, With Cord, Less Accessory	3 / 16 GA	1.31	9	300	13	6	1
	PC10-3012-X		3 / 12 GA	3.31	9	300	20	8	1
	PC10L-3016	Less Hose, Less Cord,	3 / 16 GA	1.31	9	300	13	5	1
	PC10L-3012	Less Accessory	3 / 12 GA	3.31	9	300	20	5	1

**COXREELS**<sup>®</sup> PC<sup>10</sup> Series Power-Cord Series is a unique compact addition to our original line of power cord and light reels. This ground-breaking design sets a new bar as the ideal cord management solution capable of fulfilling any commercial or industrial application where space is limited. Modeled after the LG "Little Giant" Series, this Series is equipped with a continuous radius grommet style power cord guide and a unique C-PEP<sup>TM</sup> Composite hub featuring excellent

chemical resistance and additional strength at cold temperatures.

FOR INDOOR USE ONLY! All models rated at 115 volts, 60 hz single phase only.

#### \*Consult factory with 4 conductor requirements.

# REEL DIMENSIONS Technical Data Sheets Available On Website







