SS SERIES

STAINLESS STEEL SPRING RETRACTABLE HOSE REELS



SS SERIES - SPRING :: REEL SPECIFICATIONS

- · Non-corrosive external fluid path with machined from high quality stainless steel 90° full-flow NPT swivel inlet
- · Swivel Seals: NITRILE Non-Toxic Food Grade Grease

DESIGN & STRUCTURE

- · Electro-polished stainless steel finish
- · Each of these reels is built of their standard series with their own unique features & benefits

- · See page 11 For P Series spring driven features
- · See page 12 For SH & MP Series spring driven features
- · See page 13 For T Series spring driven features
- · See page 16 For EN Series spring driven features

SIGNATURE FEATURES

- · Professional grade heavy duty steel construction
- Durable proprietary CPC[™] powder coat process
- · Rolled edges & ribbed discs provide strength & safety
- · Leading 2-year manufacturer's limited warranty
- · Made in the U.S.A. Sold & Supported Worldwide

POSSIBLE FIELDS OF APPLICATION

- · Corrosive Environments
- · Hygienic Environments
- · Medical Services
- · Marine/Docks/Offshore
- · Manufacturing Plants & Facilities
- · Pulp & Paper Plants
- · Food & Chemical **Processing Plants**
- · Bottling Plants

- Dairies
- · Meat Packing
- · Grocery Stores
- · Restaurants & Commercial Kitchens
- Water Treatment & Supply
- Petrochemical
- · Food Grade Washdown

ACCESSORIZE YOUR REEL :: PG 50

- 0-Rings & Swivels
- · Mounting Brackets
- Hoses
- Assorted Reel Accessories

COXREELS® SS Series "Stainless Steel" spring drivenhose reels have similar features to their related series, but are constructed of high quality electro-polished stainless steel with stainless steel fluid paths. They offer clean, non-corrosive performance in applications that require it, such as food and chemical processing, marinas, and anywhere that rust, corrosion and contamination thrive.

PSERIES-Spring Rewind

LESS HOSE						
MODEL	I.D. mm	O.D. mm	LENGTH m	BAR	Kg.	SIZE INDEX
P-LPL-335-SS	10	17	11	21	15	1
P-LPL-350-SS	10	17	15	21	18	1
P-LPL-425-SS	13	21	8	21	18	2

SH, & MP SERIES -Spring Rewind

LESS HOSE						
MODEL	I.D. mm	O.D. mm	LENGTH m	BAR	Kg.	SIZE INDEX
SHL-N-350-SS	10	17	15	21	20	3
SHL-N-450-SS	13	21	15	21	21	3
SHL-N-525-SS	19	29	8	21	20	4
MPL-N-350-SS	10	16	15	207	24	3
MPL-N-450-SS	13	19	15	172	24	3

TSERIES -Spring Rewind

LESS HOSE						
MODEL	I.D. mm	O.D. mm	LENGTH m	BAR	Kg.	SIZE
TSHL-N-4100-SS	13	21	30	21	36	5
TSHL-N-550-SS	19	29	15	21	32	6

EN SERIES -Spring Rewind

LESS HOSE						
MODEL	I.D. mm	O.D. mm	LENGTH m	BAR	Kg.	SIZE
ENL-N-335-SS	10	17	11	21	21	7
ENL-N-350-SS	10	17	15	21	26	8
ENL-N-450-SS	13	21	15	21	28	8

REEL DIMENSIONS Technical Data Sheets Available On Website

SIZE INDEX	W mm	H mm	L mm	X mm	Y mm	M mm	N mm
1	171	473	435	152	152	102	127
2	178	473	435	152	152	102	127
3	210	540	495	152	152	102	127
4	238	540	495	152	152	102	127
5	238	648	610	203	229	178	203
6	251	648	610	203	229	178	203
7	175	479	483	152	152	102	127
8	216	552	556	152	152	102	127
	Overall Dimensions			Ba	se —	Mountin	Pattern —



