
# 100W & 1275W SERIES

# LARGE CAPACITY WELDING REELS



COXREELS® 100W Series "Welding" hand crank hose reels are lightweight, compact and versatile. Save time and effort while increasing the safety of your work environment. The sturdy "U" shaped frame and all steel construction make this one tough little reel.

### *100W SERIES*

		LESS HOS	SIZE								
	MODEL	I.D.	FT.	PSI	APRX. LBS.	MODEL	APRX. LBS.	INDEX			
	<b>OXYGEN-ACETYLE</b>	IF welding hose fittings.									
	112W-1-50	1/4"	50	200	28	112WL-1-50	18				
	112W-1-100	1/4"	100	200	37	112WL-1-100	18	2			
	117W-1-200	1/4"	200	200	68	117WL-1-200	30	3			
	T Grade welding hose with 9/16" – 18 UNF welding hose fittings.										
	112WT-1-50	1/4"	50	200	28	112WTL-1-50	18	1			
	112WT-1-100	1/4"	100	200	37	112WTL-1-100	18	2			
-	117WT-1-200	1/4"	200	200	68	117WTL-1-200	30	3			

**COXREELS®** 1275W Series hand crank or motorized "Welding" hose reels are built to manage long lengths of bulky twin line welding hose. The direct bevel gear drive, low profile outlet riser and open drum slot design are features greatly appreciated by the regular user. Dual brass swivel inlets on each side of the reel assure full flow trouble free performance.

# 100W & 1275W SERIES :: REEL SPECIFICATIONS

#### 100W SWIVEL

- External 90° full-flow dual ported brass swivel offering both connections from the same side of the reel
- Swivel seals: VITON®

## 100W DESIGN & STRUCTURE

- · Compact solid one piece, heavy gauge steel "U" shaped frame with open drum design
- · Composite bearing for smooth rotation
- · Adjustable tension brake to prevent "free-wheeling" during operation, transport or storage

#### 100W RETRACTION

· Direct hand crank rewind

#### 1275W SWIVEL

- Two machined from solid brass 90° full-flow 3/8" NPT swivel inlets (One on each side of the reel)
- Swivel Seal: VITON®

#### 1275W DESIGN & STRUCTURE

- All welded steel "A" frame construction for superior
- Exclusive low profile outlet risers & open drum slot design for flat smooth hose wrap
- · Permanently lubricated self-aligning pillow block bearings for trouble-free & smooth rotation

#### 1275W RETRACTION

· Choice of motor or bevel gear hand crank

#### SIGNATURE FEATURES

- Professional grade heavy duty steel construction
  Durable proprietary CPC™ powder coat process
- · Rolled edges & ribbed discs provide strength & safety
- · Leading 2-year manufacturer's limited warranty
- · Made in the U.S.A. Sold & Supported Worldwide

#### POSSIBLE FIELDS OF APPLICATION

- · Manufacturing Plants & Facilities
- · Maintenance, Repair & Operations
- · Welding / Service Trucks Welding Shops
- Automotive & Fleet Maintenance
- Garage Settings
- · Mining, Construction & Railroad Operations
- **Offshore**

# ACCESSORIZE YOUR REEL :: PG 52

- 0-Rings & Swivels
- · Roller Brackets

- Pipelines
- Marine/Ship Building/

#### Hoses Assorted Reel Accessories

IZ/JW JENI	- 0xy-	Acetylene weld	ing hose with	9/16" – 18 UI	NF welding hose fittings					
	HO	SE			LESS HOSE		SIZE			
MODEL I.D.		FT. PSI		APRX. LBS.	MODEL	APRX. LBS.	INDEX			
<b>OXYGEN-ACETYLE</b>	VE	0xy-Acetylen	e welding hos	e with <sup>9</sup> /16" –	18 UNF welding hose fittings.					
1275W-3-100-X	3/8"	100	200	73	1275WL-3-100-X	45	4			
1275W-3-150-X	3/8"	150	200	90	1275WL-3-150-X	48	5			
1275W-3-250-X	3/8"	250	200	126	1275WL-3-250-X	56	6			
-	3/8"	350	200	-	1275WL-3-350-X	64	7			
OTHER FUELS T Grade welding hose with 9/16" – 18 UNF welding hose fittings.										
1275WT-3-100-X	3/8"	100	200	73	•	-	4			
1275WT-3-150-X	3/8"	150	200	90	•	-	5			
4075WT 2 050 V	36"	250	200	100						

# - SUFFIX "X" OPTIONS

1975III CEDIEC

When ordering, substitute the "X" with selection below, NOTE: Add 5 lbs to ship weight if reel is crated

3,					
SUFFIX	TYPE	DESCRIPTION	ADD ON APRX. LBS		
A	AIR - 4 VANE	ALUMINUM BODY AIR MOTOR	8		
C	FRONT HAND CRANK	BEVEL GEARED CRANK	3		
Н	HYDRAULIC	END PORTED 9/16-18 UNF	6		

# **REFI DIMENSIONS** Technical Data Sheets Available On Website

Technical Data Sheets Available On Website										
OLZE INDEV	W		Н			٧.	Υ		~	
SIZE INDEX	CRANK	ELEC.	CRANK	ELEC.		Х	CRANK	ELEC.	Ø	Dw
1	15 <sup>1</sup> /4"	-	13"	-	12"	6"	6"	-	51/2"	41/2"
2	183/4"	-	13"	-	12"	91/2"	6"	-	51/2"	8"
3	18 <sup>1</sup> /4"	-	18"	-	17"	91/2"	6"		51/2"	8"
4	187/8"	197/8"	185⁄8"	191/8"	175⁄8"	133/8"	153/8"	16"	61/4"	8"
5	227/8"	237/8"	185⁄8"	191/8"	175⁄8"	173/8"	153/8"	16"	61/4"	12"
6	287/8"	297/8"	185⁄8"	191/8"	175⁄8"	233/8"	153/8"	16"	61/4"	18"
7	347/8"	357/8"	185⁄8"	191/8"	175/8"	293/8"	153/8"	16"	61/4"	24"

