

1/2" - 1" I.D.

# SS 100, 1125 & 1175 SERIES STAINLESS STEEL HAND CRANK & MOTORIZED HOSE REELS



1125-4-200-SP  
with "SP" Finish

112-4-75-SS  
with "SS" Finish

## SS SERIES - HAND CRANK/ MOTORIZED:: REEL SPECIFICATIONS

### SWIVEL

- Non-corrosive machined from high quality stainless steel 90° full-flow NPT swivel inlet
- Swivel Seals: NITRILE Non-Toxic Food Grade Grease

### DESIGN & STRUCTURE

- Choice of stainless steel finish includes:  
 "SP" Standard unpolished "as manufactured" stainless steel finish  
 "SS" Electro-polished stainless steel finish
- Each of these reels is built of their standard series with their own unique features & benefits

### RETRACTION

- See page 36 for 100 Series features
- See page 40 for 1125 Series features
- See page 41 for 1175 Series features

### SIGNATURE FEATURES

- Professional grade heavy duty steel construction
- Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- Made in the U.S.A. - Sold & Supported Worldwide

### POSSIBLE FIELDS OF APPLICATION

- |                                     |                                     |
|-------------------------------------|-------------------------------------|
| • Corrosive Environments            | • Bottling Plants                   |
| • Hygienic Environments             | • Dairies                           |
| • Fire Suppression                  | • Meat Packing                      |
| • Medical Services                  | • Grocery Stores                    |
| • Marine/Docks/Offshore             | • Restaurants & Commercial Kitchens |
| • Manufacturing Plants & Facilities | • Water Treatment & Supply          |
| • Pulp & Paper Plants               | • Petrochemical                     |
| • Food & Chemical Processing Plants | • Food Grade Washdown               |

### ACCESSORIZE YOUR REEL :: PG 52

- |                     |                             |
|---------------------|-----------------------------|
| • O-Rings & Swivels | • Hoses                     |
| • Roller Brackets   | • Assorted Reel Accessories |
| • Stacking Brackets |                             |

**COXREELS® SS Series "Stainless Steel" hand crank hose reels have similar features to their related series, but are constructed of high quality electro-polished or unpolished as manufactured stainless steel with stainless steel fluid paths.** They offer clean, non-corrosive performance in applications that require it, such as food and chemical processing, marinas, and anywhere that rust, corrosion and contamination thrive.

## SS SERIES

- ALL REELS SUPPLIED LESS HOSE

LESS HOSE										SIZE INDEX
MODEL	I.D.		O.D.	FT.	PSI	APRX. LBS.				
SS100 SERIES - Hand Crank - SS100 Series is only available in SS finish.										
112-4-75-SS	1/2"		7/8"	75	4,000	21		1		
117-4-225-SS	1/2"		7/8"	225	4,000	31		2		
117-5-100-SS	3/4"		1 1/4"	100	4,000	36		3		
LESS HOSE										SIZE INDEX
MODEL	STANDARD CAP			OPTIONAL CAP. Reducer required			INLET SWIVEL & OUTLET RISER	PSI	APRX. LBS.	
	I.D.	O.D.	FT.	I.D.	O.D.	FT.				
SS1125 SERIES - Hand Crank & Motor Driven										
1125-4-100-X	1/2"	7/8"	100	3/8"	3/4"	140	1/2" F NPT	3,000	36	4
1125-4-200-X	1/2"	7/8"	200	3/8"	3/4"	300	1/2" F NPT	3,000	39	5
1125-5-100-X	3/4"	1 1/4"	100	1/2"	7/8"	200	3/4" F NPT	3,000	42	6
1125-5-200-X	3/4"	1 1/4"	200	1/2"	7/8"	450	3/4" F NPT	3,000	55	7
SS1175 SERIES - Hand Crank & Motor Driven										
1175-6-100-X	1"	1 7/16"	100	3/4"	1 1/4"	150	1" F NPT	3,000	70	8
1175-6-200-X	1"	1 7/16"	200	3/4"	1 1/4"	300	1" F NPT	3,000	83	9

→ Designate either SP or SS for choice of finish

## MOTOR OPTIONS

When ordering, suffix the model number with selection below. NOTE: Add 5 lbs to ship weight if reel is crated

SUFFIX	TYPE	DESCRIPTION	ADD ON APRX. LBS
<b>A</b>	AIR - 4 VANE	ALUMINUM BODY AIR MOTOR	8
<b>AB</b>	AIR - 6 VANE	CAST IRON AIR MOTOR	8
<b>C</b>	FRONT HAND CRANK	BEVEL GEARED CRANK	3
<b>E</b>	12 V DC, 1/3 HP	REVERSIBLE	13
<b>ED</b>	12 V DC, 1/2 HP EXP.	EXPLOSION PROOF, REVERSIBLE	26
<b>EF</b>	24 V DC, 1/3 HP	REVERSIBLE	13
<b>EB</b>	24 V DC, 1/2 HP EXP.	EXPLOSION PROOF, REVERSIBLE	26
<b>EA</b>	115 V AC, 1/2 HP EXP.	EXPLOSION PROOF REVERSIBLE AC RECTIFIED	26
<b>EJ</b>	230 V AC, 1/2 HP EXP.	EXPLOSION PROOF REVERSIBLE AC RECTIFIED	26
<b>H</b>	HYDRAULIC	END PORTED 9/16-18 UNF	6

## REEL DIMENSIONS

Technical Data Sheets Available On Website

SIZE INDEX	W			H			L	X	Y		Ø	Dw
	CRANK	ELEC.	AIR / HYD.	CRANK	ELEC.				CRANK	ELEC.		
<b>1</b>	22 3/4"	-	-	13"	-	12"	14"		6"	-	5 1/2"	12 1/2"
<b>2</b>	22 3/4"	-	-	18"	-	17"	14"		6"	-	5 1/2"	12 1/2"
<b>3</b>	23 1/4"	-	-	18"	-	17"	14"		6"	-	5 1/2"	12 1/2"
<b>4</b>	19 1/2"	19 3/4"	17"	18 3/4"	19 1/4"	17 5/8"	11 3/8"	15 3/8"	15 3/8"	16"	6 1/4"	6"
<b>5</b>	25 1/2"	25 3/4"	23"	18 3/4"	19 1/4"	17 5/8"	17 3/8"	15 3/8"	15 3/8"	16"	6 1/4"	12"
<b>6</b>	26 3/4"	26"	23 3/8"	18 3/4"	19 1/4"	17 5/8"	17 3/8"	15 3/8"	15 3/8"	16"	6 1/4"	12"
<b>7</b>	38 3/4"	38"	35 3/8"	18 3/4"	19 1/4"	17 5/8"	29 3/8"	15 3/8"	15 3/8"	16"	6 1/4"	24"
<b>8</b>	28 1/8"	26"	24 1/2"	26 1/8"	26 1/8"	24"	17"	20 1/8"	20 1/8"	20 1/8"	10 1/2"	11 1/2"
<b>9</b>	36 5/8"	34 1/2"	33"	26 1/8"	26 1/8"	24"	25 1/2"	20 1/8"	20 1/8"	20 1/8"	10 1/2"	20"
Overall Dimensions												
Base												
Drum												

