## HAND CRANK & MOTORIZED REELS

## **ACCESSORIES**

MODEL UPGRADES & ADDITIONS			AVAILABLE FOR SERIES								
		PART NO.	100	1125	1175	1185	1195	1275	1600		
-dro	Spring Loaded Lock Pin The spring-loaded lock pin assembly is designed to lock &	9077	•								
1	secure the reel, even in mobile conditions over rough terrain.	20843		•	•	•	•	•	•		
LOCK FREE REWIND	3-Way Pin Lock Kit 3 Positions - Pin locks reel with heavy duty 3/4' solid steel spin. Disengages for free unwind. Can be used to activate switch for electric rewind.	16702							•		
1	Universal Bracket Kit 4 various positions 0°, 30°, 60°, 90° for mounting bevel crank on either side of the reel. Includes removable center guard cap for easy bearing access. Made from powder coated steel.	16400							•		
		7406		•							
	Gear Guards Guards beveled gears or chain & sprocket from dirt & foreign matter, while also protecting operator from injury.	7700 24" disc size			•						
OTI		8176 8176-1	_		_		•	_			
		24" disc size				•					
		8176-2 28" disc size				•					
		16601-122 20" disc size							•		
100		16602-138 24" disc size							•		
		16602-180 28" disc size							•		
	Lower Chain Guards	<b>16620</b> 20" disc size						•			
	Guard access to chain from side of reel. Includes bracket to cover access to chain from front of reel	<b>16624</b> 24" disc size							•		
	from gap between disk & frame.	<b>16628</b> 28" disc size							•		
446	Idler Gear Reduce drum speed & increase torque. Available in three sizes,	17250-2 (1:2 ratio)					•		•		
		17250-3 (1:3 ratio)					•		•		
	they are factory installed on the motor kits.	17250-4 (1:4 ratio)					•		•		
	Brawny Reel Upgrade Available for 1125 Series for 3,000 PSI (BX) or 5,000 PSI (BH) - 10 gauge plates welded into each disc to keep them from bowing.	Prefix model <b>BX</b>	•	•							
	Prevents deformation & eventual crushing of the drum that can be caused by hose pressure.     The center drum has been thickened from 16GA to 14GA.	Prefix model <b>BH</b>		•							
QI_	High Temperature Drag Brake For 1/2" models	7429-1-4	•								
	High Temperature Drag Brake For 3/4" models	7429-1-5		•							
9	3 Way Brake A 3-position brake with lock, friction & free spinning positions. Easily clears brackets & guards for gloved-hand operation. In locked position, does not protrude past front of reel.	16703							•		
	Heavy Duty Band Brake			•	•						
<b>%</b>	Steel band lined with brake friction material. Tension is adjusted with a wing nut or a knob by hand (no tools required).  - Increased braking power - Increased brake life.	8302				•					
		<b>8302-1</b> 90° Swivel				•					
	<ul> <li>Easier &amp; more precise brake adjustment (control).</li> </ul>	16705							•		

MODEL UPGRADES & ADDITIONS		PART NO.	AVAILABLE FOR S						
		PART NU.	1125	1175	1185	1195	1275	1600	
	Wand Holder  - Lightweight aluminum construction with black CPCTM powder finish 24" long with a 1.6" diameter, ideal to store pressure washing guns & other spraying devices Left, right, front & rear sides mount configuration.	15735	•						
*	Bevel Crank Handle Holster Universal design mounts to either side of the reel with independent mounting holes. Features chained retaining pin to keep handle in place.	16704		•	•	•	•	•	
	Hose Strain Relief Kit	HSRK-050 1/2" Hose	•						
		HSRK-075 3/4" Hose	•	•*					
	against the drum.  The clamp provides a strain relief when the hose is fully extended	HSRK-100 1" Hose	•	•			•		
	from the reel.	HSRK-100F 1" Forestry Hose	•	•					
		HSRK-125 11/4" Hose			•*				
		HSRK-150 11/2" Hose			•	•*			

\* With reducer (optional cap)

AVAILABLE FOR SERIES

1125

1175

1275

PART NO.

**PR-1125-6** 1125-4-100 1125-5-50

PRP-1125-6

**PR-1125-12** 1125-4-200 1125-4-200-BYXX 1275-4-100



## Portable Cart

PORTABLE HOSE REEL CART

Steel round handle detaches for compact storage. Steel front legs with rubber feet prevent sliding. High grade ball bearings with hardened cup. 1/2" diameter steel axle. Solid 8" rubber tires. For 8" semi-pneumatic tires order part number begining with PRP. Weight: 17 lbs.

12/3-4-100				
<b>PRP-1125-12</b> 1125-4-200 1125-4-200-BYXX 1275-4-100	•			•
PR-1175-11 1175-6-100 1175-6-100-BYXX 1185-1124		•	•	
<b>PRP-1175-11</b> 1175-6-100 1175-6-100-BYXX 1185-1124		•	•	
PR-1175-15 1175-6-150 1185-1524		•	•	
PRP-1175-15 1175-6-100 1185-1524		•	•	
PR-1125-HC	•			



Carry Handles
Easily bolts to "A" frame making the reel portable. 1" tube steel construction.
Powder coated crinkle black.
Weight: 8 lbs.