

1/4" - 1/2" I.D.

EZ-SG & EZ-SGW SERIES

**SIDE MOUNT HOSE REELS
WITH GUIDE ARM**



COXREELS® EZ-SG & EZ-SGW Series expand the capabilities of the "Side Mount" spring driven hose reels, adding a multi-position guide arm for maximum and convenient hose control. Ideal for tight spaces, the versatile EZ-SG Series (for air/water, oil and grease) and EZ-SGW Series (for oxy-acetylene and T Grade gas welding hose) features a simple two-bolt mounting pattern for easy installation and detachment on any vertical flat surface. Common applications include service vehicles, tool benches, vertical walls and beams, vehicle lift systems, machine tools, and many more. The guide arm and roller assembly are easily moved to one of the six different positions with a standard 1/2" wrench.

APPLICATIONS

- Air/Water Services
- Pneumatic Tools
- Welding Shops
- Service/Mechanic/Utility Vehicles
- Lubrication
- Chemical Fluid Transfer
- General Industrial
- Construction Sites

EZ-SG SERIES :: REEL SPECIFICATIONS

SWIVEL

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Zinc plated steel swivel on HP models)
- Swivel Seals: NITRILE
- External fluid path with 90° full-flow dual ported brass swivel offering both connections from the same side of the reel (On EZ-SGW Models)
- Swivel Seals: VITON® (On EZ-SGW Models)

DESIGN & STRUCTURE

- Side mount design for vertical flat surface, cabinet, or enclosed space mounts
- Adjustable, six position guide arm & roller assembly provide maximum hose control
- 2-bolt mounting pattern easily mounts & detaches for temporary or permanent installation
- Solid, one piece, 3/16" steel arm base for maximum stability
- 1" solid steel axle & lubricated precision bearings for smooth rotation

EZ-COIL® RETRACTION

- **OUR PATENTED SAFETY SYSTEM THAT RETRACTS UP TO 80% SLOWER THAN CONVENTIONAL SPRING DRIVEN REELS**
- Enclosed factory tuned & matched cartridge-style spring motor
- Non corrosive, stainless steel spring, pawl, & zinc plated ratchet
- Multi-position lock ratchet mechanism secures hose at desired length.
- Non-locking, less ratchet option available (add suffix **-BXC**)


SIGNATURE FEATURES

- Professional grade, heavy duty steel construction
- Durable proprietary CPC™ powder coat process
- Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- Made in the U.S.A. - Sold & Supported Worldwide

ACCESSORIZE YOUR REEL :: PG 17

- O-Rings & Swivels
- Hoses

- Assorted Reel Accessories



EZ-SG SERIES

Do not exceed listed hose O.D. to obtain maximum length.

HOSE						LESS HOSE		SIZE INDEX
MODEL	I.D.	O.D.	FT.	PSI	APRX. LBS.	MODEL	APRX. LBS.	
LOW PRESSURE		Models with hose are for air water service with a maximum temperature 150°F. Models less hose can be used for air, water or oil						
EZ-SG13-L125	1/4"	1/2"	25	300	25	SG13L-L125	22	1
EZ-SG13-L135	1/4"	1/2"	35	300	26	SG13L-L135	23	1
EZ-SG13-L325	3/8"	5/8"	25	300	26	SG13L-L325	23	2
EZ-SG17-L350	3/8"	5/8"	50	300	40	SG17L-L350	33	3
EZ-SG17-L430	1/2"	3/4"	30	300	42	SG17L-L430	37	3
EZ-SG19-L450	1/2"	3/4"	50	300	52	SG19L-L450	44	5
MEDIUM PRESSURE		Reels are furnished with standard one wire braid hose suitable for air, water or oil applications. Hose exceeds SAE R1 specifications. Maximum Temperature 250°F.						
EZ-SG17-M325	3/8"	1 1/16"	25	3,000	46	SG17L-M325	39	3
EZ-SG19-M350	3/8"	1 1/16"	50	3,000	63	SG19L-M350	51	5
EZ-SG17-M425	1/2"	1 3/16"	25	2,500	46	SG17L-M425	39	4
EZ-SG19-M450	1/2"	1 3/16"	50	2,500	65	SG19L-M450	51	6
HIGH PRESSURE		Reels are furnished standard with S.A.E. 100R16 #1 or #2 wire braid hose suitable for grease and hydraulic oil applications. Maximum Temperature 250°F.						
EZ-SG17-H125	1/4"	9/16"	25	5,000	45	SG17L-H125	39	4
EZ-SG19-H150	1/4"	9/16"	50	5,000	62	SG19L-H150	51	7
EZ-SG17-H325	3/8"	1 1/16"	25	4,000	46	SG17L-H325	39	4
EZ-SG19-H350	3/8"	1 1/16"	50	4,000	63	SG19L-H350	51	8

EZ-SGW SERIES

Do not exceed listed hose O.D. to obtain maximum length.

HOSE					LESS HOSE		SIZE INDEX
MODEL	I.D.	FT.	PSI	APRX. LBS.	MODEL	APRX. LBS.	
OXYGEN-ACETYLENE							
Oxy-Acetylene is twin-siemese type meeting R.M.A. and C.G.A. type V.D. grade R specifications. Use of other types of hose is not recommended.							
EZ-SG17W-150	1/4"	50	200	59	EZ-SG17WL-150	47	9
EZ-SG19W-175	1/4"	75	200	77	EZ-SG19WL-175	60	10
OTHER FUELS							
Reels with "T Grade" hoses are used for a wide variety of gases, such as MAPP, propane, natural and fuel.							
EZ-SG17WT-150	1/4"	50	200	59	EZ-SG17WTL-150	47	9
EZ-SG19WT-175	1/4"	75	200	77	EZ-SG19WTL-175	60	10

REEL DIMENSIONS

Technical Data Sheets Available On Website

SIZE INDEX	W	H	L	Y	M
1	6 1/4"	15 1/2"	13 1/2"	2 1/2"	14"
2	6 3/4"	15 1/2"	13 1/2"	2 1/2"	14"
3	6 3/4"	19 1/2"	17"	2 1/2"	18"
4	7 1/4"	19 1/2"	17"	2 1/2"	18"
5	8 1/2"	22"	19 1/2"	2 7/8"	20 1/2"
6	9 3/8"	22"	19 1/2"	2 7/8"	20 1/2"
7	9"	22"	19 1/2"	2 7/8"	20 1/2"
8	9 1/2"	22"	19 1/2"	2 7/8"	20 1/2"
9	8 7/8"	19 1/2"	17"	2 1/2"	18"
10	10 1/2"	22"	19 1/2"	2 1/2"	20 1/2"

Overall Dimensions

Base

Mounting Pattern