

EZ-PC SERIES

POWER CORD REELS

COXREELS® EZ-PC Series spring driven "Power Cord" reels are heavy duty, industrial grade power sources. They replace tangled extension cords and self-retract to increase safety, productivity, and efficiency. Modeled after the EZ-P and EZ-SH Series, the EZ-PC Series are designed for long-lasting, hassle-free performance even under the most demanding conditions.

APPLICATIONS

- Power Tools
- Light Source
- General Industrial
- Manufacturing Plants
- Workshops
- Construction Sites
- Automotive & Fleet Service Centers

EZ-PC SERIES :: REEL SPECIFICATIONS

SLIP RING

- External, heavy gauge CPC™ powder coated steel components cover for simple slip ring routine maintenance
- Electrical current runs through a 25 Amp / 600V rated slip ring (35Amp on select models)
- Include 5' lead cable & grounding plug (Except on less cord models)

DESIGN & STRUCTURE

- Selection of electrical accessories
- Single pedestal cord reel with space saving design facilitates workplace organization
- Guide arm adjusts to wall, floor, & overhead positions
- Solid one piece, heavy gauge 1/4" steel base & support post for maximum stability
- Coxreels' exclusive Super Hub™ dual axle support system on models with size index #3 & #4
- 1" solid steel axle & lubricated precision bearings for smooth rotation

EZ-COIL RETRACTION

- **OUR PATENTED SAFETY SYSTEM THAT RETRACTS UP TO 80% SLOWER THAN CONVENTIONAL SPRING DRIVEN REELS**
- Enclosed factory tuned & matched cartridge-style spring motor
- Non-corrosive, stainless steel spring, pawl, & zinc plated ratchet
- Multi-position lock ratchet mechanism secures cord at desired length

SIGNATURE FEATURES

- Professional grade, heavy duty steel construction
- Durable proprietary CPC™ powder coat process
- Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- Made in the U.S.A. - Sold & Supported Worldwide

ACCESSORIZE YOUR REEL :: PG 17

- Mounting Brackets
- Assorted Reel Accessories

UL Listed †
EUL Listed ††

EZ-PC SERIES

CORD								SIZE INDEX
MODEL	ACCESSORY	AWG / NO COND.	CORD FT.	TYPE	VOLTS	AMPS	APRX. LBS.	
FOR INDOOR USE ONLY!								
All models rated at 115 volts, 60 hz single phase only.								
EZ-PC13-5016-A	Single Industrial Receptacle† 	16 / 3	50	SJO	115	13	36	1
EZ-PC24-0016-A		16 / 3	100	SJO	115	13	73	2
EZ-PC13-5012-A		12 / 3	50	SJO	115	20	40	1
EZ-PC24-0012-A		12 / 3	100	SJO	115	20	81	2
EZ-PC13-5012-B	Quad "4 Plug" Industrial Receptacle† 	12 / 3	50	SJO	115	20	41	1
EZ-PC24-0012-B		12 / 3	100	SJO	115	20	84	2
EZ-PC13-5016-C	Fluorescent Tube Light - Shock Absorbing & Shatter Resistant† 	16 / 3	50	SJTO	115	0.3	37	1
EZ-PC24-0016-C		16 / 3	100	SJTO	115	0.3	75	2
EZ-PC13-5016-D	Fluorescent Angle Light with Tool Tap Plug† 	16 / 3	50	SJTO	115	13	37	1
EZ-PC24-0016-D		16 / 3	100	SJTO	115	13	73	2
EZ-PC13-5016-E	Incandescent Caged Drop Light with Tool Tap Plug† 	16 / 3	50	SJTO	115	13	36	1
EZ-PC24-0016-E		16 / 3	100	SJTO	115	13	73	2
EZ-PC13-5016-F	Duplex G.F.C.I. Metal Industrial Receptacle† 	16 / 3	50	SJO	115	13	38	1
EZ-PC24-0016-F		16 / 3	100	SJO	115	13	73	2
EZ-PC13-5012-F		12 / 3	50	SJO	115	20	42	1
EZ-PC24-0012-F		12 / 3	100	SJO	115	20	83	2
EZ-PC24-0016-X	With Cord, Less Accessory 	16 / 3	100**	SJO	115	13	71	2
EZ-PC13-5012-X		12 / 3	50**	SJO	115	20	40	1
EZ-PC24-0012-X		12 / 3	100**	SJO	115	20	81	2
EZ-PC13L-5016	Less Cord, Less Accessory 	16 / 3	50*	SJO	115	25	31	1
EZ-PC24L-0016		16 / 3	100*	SJO	115	25	62	2
EZ-PC13L-5012		12 / 3	50*	SJO	115	25	29	1
EZ-PC24L-0012		12 / 3	100*	SJO	115	25	64	2

REEL DIMENSIONS

Technical Data Sheets Available On Website

SIZE INDEX	W	H	L	X	Y	M	N
1	8 1/2"	14 7/8"	13 1/2"	5"	6"	3"	5"
4	10 1/4"	25 1/2"	24"	6"	6"	4"	5"

Overall Dimensions Base Mounting Pattern

