

Fire & SAFETY

PROFESSIONAL GRADE FEATURES



HEAVY DUTY SPUN DISCS WITH ROLLED EDGES - not stamped, for greater strength, made with first of its kind CNC robotic spinning cell

HIGH QUALITY STEEL CONSTRUCTION with our durable CPC™ powder coat finish

PERMANENTLY SEALED PILLOW BLOCK BEARINGS for smooth rotation

ELECTROLESS NICKEL PLATED STEEL SWIVEL, swivel seals: NITRILE

LOW PROFILE RISER & OPEN DRUM SLOT for smooth, even hose wraps. Available with NST threading for booster hose

OPTIONAL EQUIPMENT: TOP AND BOTTOM MOUNT ROLLER GUIDES

WELDED STEEL "HYBRID" FRAME offers the strength of an "A" frame with the versatility of a box frame for superior reel structure

CHOICE OF MOTOR



POSSIBLE FIELDS OF APPLICATION

- Urban & Wildland Fire Interface
- Industrial Fire Protection
- Booster Hose
- Twin Agent / CAF Units
- Hydraulic Rescue Tools
- Breathing Air
- Skid Units
- Brush Trucks
- ATVs



WWW.COXREELS.COM
INFO@COXREELS.COM

5865 S. ASH AVE
TEMPE, AZ 85283

800.COX.REEL
480.820.6396

#COXREELS





1125 SERIES

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Nickel plated steel swivel on 1" models)
- Swivel Seals: NITRILE (AFSLAS on 1" models)
- Exclusive low profile outlet riser & open drum slot design for flat smooth hose wrap. All welded steel "A" frame construction for superior reel structure


MODEL	MOTOR OPTION	I.D.	FT.	PSI	APRX. LBS.	W x H x L
1125-5-100-RXXX	Electric Motor Options Available	3/4"	100	3,000	42	26 3/4 x 18 3/4 x 17 5/8"
1125-5-200-RXXX		3/4"	200	3,000	55	38 3/4 x 18 3/4 x 17 5/8"
1125-6-50-RXXX		1"	50	3,000	55	42 3/4 x 18 3/4 x 17 5/8"
1125-6-100-RXXX		1"	100	3,000	69	32 x 18 1/2 x 17 5/8"



SP-1125 SERIES

- Non-corrosive external fluid path with machined from high quality stainless steel 90° full-flow NPT swivel inlet
- Swivel Seals: NITRILE with Non-Toxic Food Grade Grease
- Exclusive low profile outlet riser & open drum slot design for flat smooth hose wrap


MODEL	MOTOR OPTION	I.D.	FT.	PSI	APRX. LBS.	W x H x L
1125-5-100-SP	Electric Motor Options available	3/4"	100	3,000	42	26 3/4 x 18 3/4 x 17 5/8"
1125-5-200-SP		3/4"	200	3,000	55	38 3/4 x 18 3/4 x 17 5/8"



1600 SERIES

- External fluid path with nickel plated steel swivel
- Swivel Seals: NITRILE
- Exclusive low profile outlet riser, open drum slot design for flat smooth hose wrap
- All welded hybrid frame with added bolts
- Available with stainless steel 304 or 316 fluid path

MODEL	MOTOR OPTION	I.D.	O.D.	FT.	PSI	APRX. LBS.	W x H x L
1660-1520-RXXX	Electric Motor Options Available	1"	1 7/16"	100	4,000	68	31 3/8 x 21 3/4 x 20"
1660-0924-RXXX		1"	1 7/16"	100	4,000	72	35 3/8 x 25 1/4 x 24"
1160-2220-RXXX		1"	1 7/16"	165	4,000	89	35 3/8 x 21 3/4 x 20"
1660-1524-RXXX		1"	1 7/16"	165	4,000	81	31 3/8 x 25 1/4 x 24"
1660-0928-RXXX		1"	1 7/16"	165	4,000	85	25 3/8 x 29 1/4 x 28"
1660-2820-RXXX		1"	1 7/16"	200	4,000	94	43 7/8 x 21 3/4 x 20"
1660-2024-RXXX		1"	1 7/16"	200	4,000	91	35 7/8 x 25 1/4 x 24"
1660-1128-RXXX		1"	1 7/16"	200	4,000	88	27 3/8 x 29 1/4 x 28"
1680-2024-RXXX		1 1/2"	2 3/8"	100	1,500	91	33 3/8 x 25 1/4 x 24"
1680-1328-RXXX		1 1/2"	2 3/8"	100	1,500	92	26 7/8 x 29 1/4 x 28"
1680-2028-RXXX		1 1/2"	2 3/8"	150	1,500	106	33 3/8 x 29 1/4 x 28"
1680-2428-RXXX		1 1/2"	2 3/8"	200	1,500	114	37 3/8 x 29 1/4 x 28"



1275 SERIES

- Two external fluid paths with machined from solid brass 90° full-flow NPT swivel inlets (one on each side of the reel)
- Swivel Seals: NITRILE. Electroless nickel plated steel swivel.
- Two low profile outlet risers & open drum slot design for dual hose applications.

MODEL	MOTOR OPTION	I.D.	O.D.	FT.	PSI	APRX. LBS.	W x H x L
1275-6-50-RXXX	Electric Motor Options Available	1 1/2"	2 1/16"	50	600	76	25 x 26 x 24"
1275-6-75-RXXX		1 1/2"	2 1/16"	75	600	81	29 x 26 x 24"
1275-6-100-RXXX		1 1/2"	2 1/16"	100	600	94	33 1/2 x 26 x 24"



1275HP SERIES

- Two high pressure 90° full-flow melarized steel 1/4" swivel inlet
- Swivel Seals: TEFLON
- Two low profile outlet risers & open drum slot design for dual hose wrap. Sturdy all welded steel "A" frame, not bolted to strengthen the reel structure

MODEL	MOTOR OPTION	INLET	OUTLET	1/4" I.D.	3/8" I.D.	PSI	APRX. LBS.	W x H x L
1275HPL-4-8	Electric Motor	1/4"	1/2"	135'	85'	10,000	76	17 1/2 x 18 5/8 x 17 5/8"
1275HPL-4-12	Options Available	1/4"	1/2"	200'	125'	10,000	81	21 1/2 x 18 5/8 x 17 5/8"



BREATHING AIR 1125 SERIES

- Non-corrosive stainless steel air/fluid path with machined from high quality stainless steel 90° full-flow NPT swivel inlet
- Swivel Seals: NITRILE Non-Toxic Food Grade Grease
- Exclusive low profile outlet riser & open drum slot design for flat smooth hose wrap

MODEL	I.D.	FT.	PSI	APRX. LBS.	W x H x L
1125P-4-6	1/2"	100	6,000	36	19 3/4 x 18 5/8 x 17 5/8"
1125P-4-8	1/2"	150	6,000	37	21 3/4 x 18 5/8 x 17 5/8"
1125P-4-12	1/2"	200	6,000	39	25 3/4 x 18 5/8 x 17 5/8"

CHOICE OF MOTORS




PC¹⁰ SERIES

- External heavy gauge CPC™ powder coated steel component cover for simple slip ring routine maintenance
- Compact & lightweight spring driven cord reel save space & facilitate workplace organization
- Choice of electrical accessory

MODEL	ACCESSORY	AWG / NO. COND.	CORD FT.	AMPS	APRX. LBS.	W x H x L
PC10-3012-A	Single receptacle	12 / 3	30	20	17	7 3/8 x 10 5/8 x 10 1/2"
PC10-3016-A	Single receptacle	16 / 3	30	13	14	7 3/8 x 10 5/8 x 10 1/2"
PC10-3012-B	Quad receptacle	12 / 3	30	20	18	7 3/8 x 10 5/8 x 10 1/2"
PC10-3016-C	Fluorescent tube	16 / 3	30	0.3	15	7 3/8 x 10 5/8 x 10 1/2"
PC10-3016-D	Fluorescent angle light	16 / 3	30	13	16	7 3/8 x 10 5/8 x 10 1/2"
PC10-3016-E	Incandescent cage light	16 / 3	30	13	14	7 3/8 x 10 5/8 x 10 1/2"
PC10-3012-F	G.F.C.I. receptacle	12 / 3	30	20	19	7 3/8 x 10 5/8 x 10 1/2"
PC10-3016-F	G.F.C.I. receptacle	16 / 3	30	13	16	7 3/8 x 10 5/8 x 10 1/2"
PC10-3012-X	Without Accessory	12 / 3	30	20	18	7 3/8 x 10 5/8 x 10 1/2"
PC10-3016-X	Without Accessory	16 / 3	30	13	14	7 3/8 x 10 5/8 x 10 1/2"

CHOICE OF ELECTRICAL ACCESSORIES



This selection only represents a sample of products applicable in this industry. Please visit us online or consult the factory for more product options.

CF-FS-001