

Petroleum

PROFESSIONAL GRADE FEATURES



ADJUSTABLE SOLID RUBBER HOSE STOP
for lead length positioning

VERSATILE GUIDE ARM adjusts to wall,
floor, ceiling & vehicle mounting

**EXTERNAL FLUID PATH WITH FULL FLOW BRASS
NPT SWIVEL** that screws directly on
1" solid steel axle, swivel is easily
removed for fast, easy maintenance

- Viewable on opposite side




HEAVY DUTY SPUN DISCS with rolled edges for
greater strength, made with first of it's kind CNC
robotic spin cell

HIGH QUALITY STEEL CONSTRUCTION
with our durable CPC™ powder coat finish

**ENCLOSED FACTORY TUNED AND MATCHED
CARTRIDGE-STYLE SPRING MOTOR**, easily r
emoved for safe & convenient replacement

- Viewable on opposite side




**TRIPLE AXLE SUPPORT WITH SUPER HUB™ &
A FULL FRAME** increased reel strength for more
demanding applications

Only on T Series. SH Series features dual axle support

POSSIBLE FIELDS OF APPLICATION

- Fuel Storage & Dispensing System
- Fuel/Lube Trucks
- Aircraft Refueling
- DEF Storage & Dispensing Sytem
- In Plant Refueling
- Ship Refueling
- Fuel Tank Trucks
- Vehicle Refueling
- Offshore



WWW.COXREELS.COM
INFO@COXREELS.COM

5865 S. ASH AVE
TEMPE, AZ 85283

800.COX.REEL
480.820.6396

#COXREELS





DEF SERIES & FUELING REELS

FUEL SERIES

- Machined from solid brass 90° full-flow NPT swivel inlet
- Swivel Seals: NITRILE
- Fuel dispensing hose designed to convey non-aromatic fuels including diesel, kerosene, fuel oil & heating oil

DEF SERIES

- Non-corrosive stainless steel 90° full-flow NPT swivel for Diesel Exhaust Fluid (DEF) dispensing applications
- Swivel Seals: VITON®
- DEF dispensing hose designed to convey the high-purity, aqueous urea solution DEF.

FUEL MODEL	EZ-Coil® Safety Line	I.D.	FT.	PSI	APRX. LBS.	W x H x L
SHF-N-525	EZ-SHF-525	3/4"	25	300	57	9 3/8 x 25 1/2 x 19 1/2"
TSHF-N-550	EZ-TSHF-525	3/4"	50	300	91	9 7/8 x 25 1/2 x 24"
TSHF-N-635	-	1"	35	300	95	10 x 25 1/2 x 24"
TSHF-N-650	-	1"	50	300	101	12 x 25 1/2 x 24"

DEF MODEL	EZ-Coil® Safety Line	I.D.	FT.	PSI	APRX. LBS.	W x H x L
SH-N-525-DF-BBX	EZ-SH-N-525-DF-BBX	3/4"	25	300	57	8 1/4 x 21 1/4 x 24"
SH-N-550-DF-BBX	EZ-SH-N-550-DF-BBX	3/4"	50	300	76	9 7/8 x 25 1/2 x 24"
TSH-N-550-DF-BBX	EZ-TSH-N-550-DF-BBX	3/4"	50	300	91	9 7/8 x 25 1/2 x 24"



SP SERIES

- External fluid paths with machined from solid brass 90° full-flow NPT swivel inlets
- Swivel Seals: NITRILE (AFLAS on 1" models)
- Reel features a sturdy box-style frame design. Reel adjusts to wall, floor, vehicle & overhead position
- Long lasting self-lubricated flange bearings for smooth rotation
- Available in Medium Pressure
- * Supplied with fuel hose

MODEL	I.D.	O.D.	FT.	PSI	APRX. LBS.	W x H x L
SLPL-550	3/4"	1 1/16"	50	300	86	19 5/8 x 20 1/2 x 22 7/8"
SLPF-550*	3/4"	1 3/16"	50	300	107	19 5/8 x 20 1/2 x 22 7/8"
SLPL-575	3/4"	1 1/16"	75	300	117	19 5/8 x 24 1/2 x 26 3/8"
SLPL-650	1"	1 1/2"	50	300	109	19 5/8 x 24 1/2 x 26 3/8"
SLPF-650*	1"	1 1/2"	50	300	142	21 x 28 1/2 x 30 3/8"
SLPL-675	1"	1 1/2"	75	300	148	21 x 28 1/2 x 30 3/8"
SLPL-750	1 1/2"	1 13/16"	50	250	123	18 x 28 1/2 x 30 3/8"
SLPL-850	1 1/2"	2 1/16"	50	250	138	20 x 28 1/2 x 30 3/8"



1125 SERIES

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Nickel plated steel swivel on 1" models)
- Swivel Seals: NITRILE (AFLAS on 1" models)
- Exclusive low profile outlet riser & open drum slot design for flat smooth hose wrap. All welded steel "A" frame construction for superior reel structure

MODEL	MOTOR OPTION	I.D.	FT.	PSI	APRX. LBS.	W x H x L
1125-5-100	Electric Motor Options Available	3/4"	100	3,000	42	26 3/4 x 18 3/4 x 17 5/8"
1125-5-175		3/4"	175	3,000	50	32 3/4 x 18 3/4 x 17 5/8"
1125-5-200		3/4"	200	3,000	55	38 3/4 x 18 3/4 x 17 5/8"
1125-5-250		3/4"	250	3,000	59	42 3/4 x 18 3/4 x 17 5/8"
1125-6-50		1"	50	3,000	55	42 3/4 x 18 3/4 x 17 5/8"
1125-6-100		1"	100	3,000	69	32 x 18 1/2 x 17 5/8"



1175 SERIES

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet
- Swivel Seals: AFLAS
- Exclusive low profile outlet riser, open drum slot design for flat smooth hose wrap. All welded steel "A" frame construction for superior reel structure

MODEL	MOTOR OPTION	I.D.	O.D.	FT.	PSI	APRX. LBS.	W x H x L
1175-6-50	Electric Motor Options Available	1"	1 7/16"	50	3,000	67	24 1/8 x 26 1/8 x 24"
1175-6-100		1"	1 7/16"	100	3,000	70	28 1/8 x 26 1/8 x 24"
1175-6-150		1"	1 7/16"	150	3,000	75	32 1/8 x 26 1/8 x 24"
1175-6-200		1"	1 7/16"	200	3,000	83	36 5/8 x 26 1/8 x 24"



1185 SERIES

- External fluid path with in-line aluminium straight, full flow NPT swivel inlet
- Swivel Seals: NITRILE
- Exclusive low profile outlet riser, open drum slot design for flat smooth hose wrap. All welded steel "A" frame construction for superior reel structure

MODEL	MOTOR OPTION	I.D.	O.D.	FT.	PSI	APRX. LBS.	W x H x L
1185-1124	Electric Motor Options Available	1 1/2"	2 1/16"	50	600	76	25 x 26 x 24"
1185-1524		1 1/2"	2 1/16"	75	600	81	29 x 26 x 24"
1185-2024		1 1/2"	2 1/16"	100	600	94	33 1/2 x 26 x 24"
1185-2528		1 1/2"	2 1/16"	150	600	122	38 1/2 x 30 x 28"



1195 SERIES

- External fluid path with in-line aluminium straight, full flow NPT swivel inlet
- Swivel Seals: VITON®
- Exclusive low profile outlet riser, open drum slot design for flat smooth hose wrap. All welded steel "A" frame construction for superior reel structure

MODEL	MOTOR OPTION	I.D.	O.D.	FT.	PSI	APRX. LBS.	W x H x L
1195-932-C	Electric Motor Options Available	2"	2 9/16"	50	600	128	22 3/4 x 33 1/4 x 32"
1195-1332-C		2"	2 9/16"	75	600	148	26 3/4 x 33 1/4 x 32"
1195-2032-C		2"	2 9/16"	115	600	186	30 3/4 x 33 1/4 x 32"

CHOICE OF MOTORS



SD SERIES

- Available with 7 strand x 7 wire galvanized steel
- Models SD-XX-1 & SDH-XXX-1 come with 7 strand x 7 stainless steel cable
- High visibility orange vinyl cable cover
- Compact static discharge cable reel available in spring rewind or direct hand crank retraction
- Non corrosive stainless steel spring, pawl & zinc plated ratchet

MODEL	EZ-Coil® Safety Line	O.D.	FT.	APRX. LBS.	W x H x L
SD-50	EZ-SD-50	5/32"	50	20	3 7/8 x 11 1/2 x 11"
SD-75	EZ-SD-75	5/32"	75	31	4 x 15 x 14 1/2"
SD-100	EZ-SD-100	5/32"	100	32	4 x 15 x 14 1/2"
SD-50-1	EZ-SD-50-1	5/32"	50	20	3 7/8 x 11 1/2 x 11"
SD-75-1	EZ-SD-75-1	5/32"	75	31	4 x 15 x 14 1/2"
SD-100-1	EZ-SD-100-1	5/32"	100	32	4 x 15 x 14 1/2"
SDH-100	-	5/32"	100	24	5 3/4 x 11 1/2 x 11"
SDH-200	-	5/32"	200	28	5 3/4 x 11 1/2 x 11"
SDH-100-1	-	5/32"	100	24	5 3/4 x 11 1/2 x 11"
SDH-200-1	-	5/32"	200	28	5 3/4 x 11 1/2 x 11"