


FEATURE FOCUS MOTORIZED CORD REEL

(5

EXPLODED ASSEMBLY:



FEATURES & BENEI

STEEL CONSTRUCTION

High-Quality steel construction provides superior strength and durability for heavy-duty applications in commercial and industrial settings.

1 CHOICE OF MOTOR

Customize reel to specific application:

Motor A	Air - 4 VANE Aluminum Body Air Motor	8 lbs
Motor AB	Air- 6 VANE Aluminum Body Air Motor	8 lbs
Motor E	Elec 12V DC 1/3 HP Reversible	13 lbs
Motor EF	Elec 24V DC 1/3 HP Reversible	13 lbs
Motor EB	24v DC 1/2 HP EXP. Explosion Proof Reversible	26 lbs
Motor ED	12v DC 1/2 HP EXP. Explosion Proof Reversible	26 lbs
Motor EA	115V AC 1/2 HP EXP. Explosion Proof Reversible, AC Rectified	26 lbs
Motor EJ	230V AC 1/2 HP EXP. Explosion Proof Reversible, AC Rectified	26 lbs
Motor H	Hydraulic End Ported 9/16-18 UNF	6 lbs



F & FF

EB. ED.

EA & EJ

2

PILLOW BLOCK BEARINGS

Pillow Block Bearings - Sturdy permanently lubricated and self-aligning pillow block bearings for smooth rotation and trouble-free operation.

- Robust lubricated horizontal surface mount bearings on 1-1/2" and 2" hose I.D models.



www.COXREELS.com

INFO@COXREELS.COM

Integrated anti-rotation cable keeper prevents the 5 foot lead cable from whipping or twisting.

ACCESSORIES GR P ES 2









GUARDS

5865 S. ASH AVE TEMPE, AZ 85283



CPC[™] Powder Coat. Long lasting, chip resistant and rust inhibiting CPC[™] powder coat finish seals all steel components for maximum corrosion resistance.

4 "A" FRAME

Sturdy one piece, all CNC robotically welded 1/4" steel "A" frame base, not bolted, for superior reel structure and narrow width for convenient installation in restricted spaces

Mounting Pattern - Mounting pattern located in the steel base for easy reel installation and detachment.

5 DIRECT DRIVE MOTOR

A solid steel halo is welded to the disc for a safe and reliable

direct gear drive retraction on 1125 and 1275 Series.

- Lubricated chain and zinc plated steel sprocket on larger motorized 1175, 1185 and 1195 Series.

SLIP RING ASSEMBLY 6

Drum-located slip ring assembly with easy to access removable panel for simple routine maintenance.

- Available with 30AMP or 45AMP, 600V rated slip ring assembly.



7

800.COX.REEL

480.820.6396

CNC SPUN DISC

Heavy duty CNC robotically spun and ribbed discs with rolled edges for greater strength, durability, cord protection and operator safety.

f



in



0



FF-MDCR-01