

1/4" - 1/2" I.D.

EZ-P SERIES PERFORMANCE HOSE REELS



COXREELS® EZ-P Series "Performance" spring driven hose reels have a long history of dependability and hassle free performance. Their compact space-saving size and heavy duty construction make them highly versatile and virtually indestructible. Time-tested proven components, superior design and craftsmanship have contributed to it's worldwide reputation as the most trusted hose reel.

EZ-P SERIES

Do not exceed listed hose O.D. to obtain maximum length.

HOSE						LESS HOSE		SIZE INDEX
MODEL	I.D.	O.D.	FT.	PSI	APRX. LBS.	MODEL	APRX. LBS.	
LOW PRESSURE						Models with hose are for air water service with a maximum temperature 150°F. Models less hose can be used for air, water or oil.		
EZ-P-LP-125	1/4"	1/2"	25	300	27	EZ-P-LPL-125	24	1
EZ-P-LP-135	1/4"	1/2"	35	300	28	EZ-P-LPL-135	25	1
EZ-P-LP-150	1/4"	1/2"	50	300	40	EZ-P-LPL-150	35	3
EZ-P-LP-325	3/8"	5/8"	25	300	28	EZ-P-LPL-325	25	2
EZ-P-LP-330	3/8"	5/8"	30	300	37	EZ-P-LPL-330	33	3
EZ-P-LP-335	3/8"	5/8"	35	300	38	EZ-P-LPL-335	34	3
EZ-P-LP-350	3/8"	5/8"	50	300	43	EZ-P-LPL-350	36	3
EZ-P-LP-430	1/2"	3/4"	30	300	45	EZ-P-LPL-430	40	4
EZ-P-LP-450	1/2"	3/4"	50	300	48	EZ-P-LPL-450	43	4
MEDIUM PRESSURE						Reels are furnished with standard one wire braid hose suitable for air, water or oil applications. Hose exceeds SAE R1 specifications. Maximum Temperature 212°F. (If used with water, synthetic fluids 135°F max.)		
EZ-P-MP-425	1/2"	13/16"	25	2,500	49	EZ-P-MPL-425	42	4
EZ-P-MP-430	1/2"	13/16"	30	2,500	51	EZ-P-MPL-430	43	4
HIGH PRESSURE						Reels are furnished standard with S.A.E. 100R16 #1 or #2 wire braid hose suitable for grease and hydraulic oil applications. Maximum Temperature 212°F. (If used with water, synthetic fluids 135°F max.)		
EZ-P-HP-125	1/4"	9/16"	25	5,000	48	EZ-P-HPL-125	42	4
EZ-P-HP-325	3/8"	11/16"	25	4,000	49	EZ-P-HPL-325	42	4

EZ-P SERIES :: REEL SPECIFICATIONS

SWIVEL

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Zinc plated steel swivel on HP models)
- Swivel Seals: NITRILE

DESIGN & STRUCTURE

- Sturdy, single pedestal reel with space saving design facilitates workplace organization
- Guide arm adjusts to wall, floor, vehicle, & overhead positions
- Solid, one piece, heavy gauge 1/4" steel base & support post for maximum stability
- 1" solid steel axle & lubricated precision bearings for smooth rotation

EZ-COIL RETRACTION


- **OUR PATENTED SAFETY SYSTEM THAT RETRACTS UP TO 80% SLOWER THAN CONVENTIONAL SPRING DRIVEN REELS**
- Enclosed, factory tuned & matched cartridge-style spring motor
- Non-corrosive, stainless steel spring, pawl, & zinc plated ratchet
- Multi-position lock ratchet mechanism secures hose at desired length

REEL DIMENSIONS

Technical Data Sheets Available On Website

SIZE INDEX	W	H	L	X	Y	M	N
1	5 7/8"	14 7/8"	13 1/2"	5"	6"	3"	5"
2	6 1/2"	14 7/8"	13 1/2"	5"	6"	3"	5"
3	6 3/4"	18 5/8"	17 1/8"	6"	6"	4"	5"
4	7"	18 5/8"	17 1/8"	6"	6"	4"	5"

Overall Dimensions Base Mounting Pattern



TOP REQUESTED UPGRADES & ACCESSORIES

SEE PAGE 17 FOR ADDITIONAL ACCESSORIES

UPGRADE TO NITRILE OR RUBBER HOSE

NITRILE HOSE: Premium high quality, oil resistant, multi-purpose hose. The high tensile spiral synthetic yarn reinforcement provides excellent kink resistance. Temperature range: -20° F to +212° F.

SYNTHETIC RUBBER HOSE: Versatile general purpose hose. The synthetic rubber tube and cover resists heat, sunlight, ozone, and weathering. Temperature range -40° F to +212° F.

UPGRADE TO STAINLESS STEEL SWIVEL

Based on the upgraded medium pressure swivel, the stainless steel swivel is machined from solid 316 stainless steel and features increased wall thicknesses with upgraded seals and backup rings.

UPGRADE TO SOLID ROLLERS

Heavy duty machined from solid plastic rollers.

ADD AIR TOOL KIT

BEND RESTRICTOR: Designed to limit the degree of bending without compromising the integrity of the hose assembly while also preventing the hose-end from kinking, excessive wearing, and tearing. Available for low pressure models.

QUICK DISCONNECT: Quick disconnect couplings tread onto end of hose fitting to provide fast, leak-proof connections for low pressure hose lines.

ADD BEND RESTRICTOR

Designed to limit the degree of bending without compromising the integrity of the hose assembly while also preventing the hose-end from kinking, excessive wearing, and tearing. Available for low pressure models.

WARNING: Cancer and reproductive Harm – See page 19 for more information – www.P65Warning.ca.gov

