P-WC SERIES

SPRING DRIVEN WELDING CABLE REELS



P-WC SERIES :: REEL SPECIFICATIONS

- External, easily accessible heavy gauge CPC™ powder coated steel components cover for simple slip ring routine maintenance
- · Electrical current runs through a 450 AMP rated slip ring

- · Designed for electrode & grounding lead applications (each lead requires an individual reel)
- · Single pedestal reel with space saving design facilitates workplace organization
- · Welding cable clamp available (see below)
- · Guide arm adjusts to wall, floor, vehicle & overhead positions
- · Solid one piece, heavy gauge 1/4" steel base & support post for maximum stability
- 1" solid steel axle & lubricated precision bearings for smooth rotation

RETRACTION

- · Enclosed factory tuned & matched cartridge-style spring motor
- · Non corrosive stainless steel spring, pawl & zinc plated ratchet
- · Multi-position lock ratchet mechanism secures cable at desired length

SIGNATURE FEATURES

- · Professional grade heavy duty steel construction
- Durable proprietary CPC[™] powder coat process
- · Rolled edges & ribbed discs provide strength & safety
- · Leading 2-year manufacturer's limited warranty
- · Made in the U.S.A. Sold & Supported Worldwide

POSSIBLE FIELDS OF APPLICATION

- · Manufacturing Plants & Facilities
- · Maintenance, Repair & Operations
- · Welding / Service Trucks
- Welding Shops
- · Garage Settings
- Automotive &
- Fleet Maintenance
- Pipelines
- · Mining, Construction & Railroad Operations
- · Marine/Ship Building/ **Offshore**

ACCESSORIZE YOUR REEL :: PG 56

- · Mounting Brackets
- · Assorted Reel Accessories

COXREELS® P-WC Series spring driven "Welding Cable" reels protect and extend the life of your welding cable by neatly and conveniently storing it on a 25, 35 or 50 foot self-retracting welding cable reel. They are the solution for keeping your work area safe, organized and efficient.

P-WC SERIES


Caution: When using reel for extended periods of time unwind all cable to prevent heat build up.


		LESS CABLE		SIZE				
MODEL	FT.	TYPE	VOLT.	AMPS.	APRX. LBS.	MODEL	APRX. LBS.	INDEX
WELDING CABLE REEL		Protect & extend the life of your welding cable while clean & organized.				keeping your work area a	nd vehicles	
P-WC13-3506	35	6GA	600	75	31	P-WC13L-3506	26	1
P-WC13-5006	50	6GA	600	75	35	P-WC13L-5006	28	1
P-WC13-3504	35	4GA	600	150	34	P-WC13L-3504	26	1
P-WC13-5004	50	4GA	600	150	39	P-WC13L-5004	28	1
P-WC13-3502	35	2GA	600	225	36	P-WC13L-3502	26	1
P-WC17-5002	50	2GA	600	225	56	P-WC17L-5002	42	2
P-WC13-2501	25	1GA	600	300	35	P-WC13L-2501	26	1
P-WC17-5001	50	1GA	600	300	60	P-WC17L-5001	42	2
P-WC13-2510	25	1/0	600	350	37	P-WC13L-2510	26	1
P-WC17-5010	50	1/0	600	350	64	P-WC17L-5010	42	2
P-WC17-3520	35	2/0	600	450	60	P-WC17L-3520	42	2
P-WC17-5020	50	2/0	600	450	68	P-WC17L-5020	42	2


REEL DIMENSIONS Technical Data Sheets Available On Website

SIZE INDEX	W	н	L	Х	Υ	M	N
1	81/2"	141/2"	133⁄4"	5"	6"	3"	5"

2 181/4 171/4" Overall Dimensions Mounting Pattern







COXREELS® ACCESSORY

Electrode Holder

Electrode holder features a six-position jaw pattern & has fully insulated, protected springs. # 7685



Grounding Clamp

300 Amp with solid copper jaws & fits cable ballpoint thru 3/0.

#7688



WARNING: Cancer and reproductive Harm - See page 63 for more information - www.P65Warning.ca.gov

