
# 314 - 1 1.0. FUEL SERIES



# FUEL SERIES :: REEL SPECIFICATIONS

#### SWIVEL

· Machined from solid brass 90° full-flow NPT swivel inlet for fuel dispensing applications. Electroless nickel plated steel swivel on 1" models · Swivel seals: Nitrile

#### HOSE

SPRING DRIVEN

C

EZ-COIL

- Fuel dispensing hose designed to convey non-aromatic fuels including diesel, kerosene, fuel oil & heating oil. Temperature Range: -20°F to +190°F
- (On -GS Models only) Fuel dispensing hose designed to convey aromatic fuels.

#### DESIGN & STRUCTURE

- · Each of these reels is built of their standard series with
- their own unique features & benefits

### Non-sparkling mechanism

#### RETRACTION

- · See page 12 for SH Series spring driven features
- See page 13 for T Series spring driven features
- See page 14 for XTM Series spring driven features
- · See page 17 for SP Series spring driven features

#### SIGNATURE FEATURES

- · Professional grade heavy duty steel construction
- Durable proprietary CPC<sup>™</sup> powder coat process
- · Rolled edges & ribbed discs provide strength & safety
- · Leading 2-year manufacturer's limited warranty
- · Made in the U.S.A. Sold & Supported Worldwide

#### POSSIBLE FIELDS OF APPLICATION DEF Storage &

- Vehicle Refueling
- Tank Trucks
- Fuel/Lube Trucks
- Fuel Storage &
- **Dispensing Systems**

# ACCESSORIZE YOUR REEL .: PG 56

- · 0-Rings & Swivels · Mounting Brackets
- Assorted Reel Accessories

**Dispensing Systems** 

· Marine/Ship Refueling/

· Aircraft Refueling

Offshore

• Hoses

- - · See page 13 for T Series dim drawings
- · See page 14 for XTM Series dim drawings



WARNING: Cancer and reproductive Harm - See page 63 for more information – www.P65Warning.ca.gov

#### FUEL HOSE T SERIES TSHF-N-535 3⁄4" 13/16" 35 300 77 EZ-TSHF-535 TSHFL-N-535 TSHF-N-550 3⁄4" 13⁄16" 50 300 83 EZ-TSHF-550 \*TSHFL-N-550 TSHF-N-575 3⁄4" 13/16 75 300 93 TSHL-N-575-BXN uel SH Series TSHF-N-635 1" 11/2" 35 300 92 TSHL-N-635-BXN TSHF-N-650 1" 1<sup>1</sup>/2" 50 300 98 TSHL-N-650-BXN FUEL HOSE XTM SERIES XTMF-LP-550 3/4" 94 11/16" 50 300 3///" XTMF-LP-550-GS 1<sup>1</sup>/16" 50 300 94 -3/4" 101 XTMF-LP-575 1<sup>1</sup>/16" 75 300 XTMF-LP-650 1" 11/2" 50 300 114 -XTMF-LP-650-GS 1" 11/2" 50 300 114 -FUEL HOSE SP SERIES SLPF-550 3⁄4" 1<sup>1</sup>/16" 50 300 99 SLPF-575 3⁄4" 1<sup>1</sup>/16" 75 300 136 **SLPF-5100**

efficiently handle fuel transfers.

FUEL HOSE SERIES

I.D. 0.D.

3⁄4" 1<sup>3</sup>⁄16"

MODEL

**FUEL HOSE SH SERIES** SHF-N-525

SPRING DRIVEN FUEL HOSE REELS

Models are equipped with fuel hose. Note: Do not exceed listed hose O.D. to obtain maximum length HOSE

> FT. PSI 1 BS

25 300

**COXREELS®** Fuel Dispensing Reels are designed to handle various non-aromatic


reels are an essential component found in utility, ground support, and bulk liquid handling transport services mounted on fuel storage & dispensing systems, fuel/lube trucks, aircraft refuelers, and tank trucks. The convenient uncoiling systems with the added hose control allow the operator to

APRX.

52

EZ-CÓIL

fuel applications including diesel, kerosene, fuel oil and heating oil. Coxreels® professional fuel dispensing reels are available in heavy-duty single pedestal (SH Series), supreme-duty dual pedestal (T Series) or box-style frame (SP Series) configurations. These fuel



\* EZ-Coil® option only available on these less hose models. Please add prefix "EZ-"

**LESS HOSE** 

MODEL

-

-

EZ-SHF-525 \*SHFL-N-525

APRX.

45

67

70

73

71

77

\_

-

-

-

1 BS

SIZE

1

2

2

3

4

3

5

5

5

6

#### **REEL DIMENSIONS** Technical Data Sheets Available On Website

		Technical Data Sheets Available On Website					
SIZE INDEX	w	н	L	Х	Y	М	N
1	9 <sup>3</sup> /8"	21¼"	19½"	6"	6"	4"	5"
2	97⁄8"	251/2"	24"	8"	9"	7"	8"
3	12"	251/2"	24"	8"	9"	7"	8"
4	10"	251/2"	24"	8"	9"	7"	8"
5	10 <sup>1</sup> ⁄8"	261⁄8"	24 <sup>1</sup> /16"	10"	15"	8 <sup>29</sup> ⁄32"	10"
6	12 <sup>3</sup> ⁄4"	261⁄8"	24 <sup>1</sup> /16"	12 <sup>3</sup> ⁄4"	15"	11 <sup>11</sup> /16"	10"
SIZE INDEX	W	Н	L	Х	Y	Ø	Dw
7	195⁄8"	201/2"	227⁄8"	153⁄8"	211⁄2"	101/2"	71⁄2"
8	195⁄8"	241/2"	263⁄8"	153⁄8"	25"	101/2"	71⁄2"
9	21"	201/2"	22 <sup>7</sup> /8"	15 <sup>3</sup> ⁄8"	21 <sup>1</sup> /2"	10 <sup>1</sup> /2"	7 <sup>1</sup> /2"
10	21"	24 <sup>1</sup> /2"	26 <sup>3</sup> ⁄8"	15 <sup>3</sup> ⁄8"	25"	10 <sup>1</sup> /2"	7 <sup>1</sup> /2"
11	21"	281/2"	303⁄8"	153⁄8"	29"	101⁄2"	71⁄2"
Overall Dimensions			Base		Mounting Pattern		

# DIMENSIONAL DRAWING

- · See page 12 for SH Series dim drawings
- · See page 17 for SP Series dim drawings

COXREELS<sup>®</sup> www.coxreels.com • 1.800.COX.REEL