# NITRO-PRO® SERIES ALUMI-PRO® SERIES

**COXREELS®** Alumi-Pro® Series "Aluminum Professional-Grade" spring driven hose reels have the strength of steel without the weight! The Alumi-Pro® series is modeled after Coxreels' popular P Series line of hose reels, but are uniquely constructed out of high quality aluminum. They're compact, lightweight and non-corrosive making them the perfect choice when polypropylene or plastic hose reels are not the preferred choice due to their limited strength and durability.

# **ALUMI-PRO® SERIES**

	LESS HO	SIZE								
MODEL	I.D.	0.D.	FT.	PSI	APRX. LBS.	MODEL	APRX. LBS.	INDEX		
LOW PRESSURE										
P-LP-125-AL	1/4"	1/2"	25	300	18	P-LPL-125-AL	15	1		
P-LP-150-AL	1/4"	1/2"	50	300	25	P-LPL-150-AL	18	3		
P-LP-325-AL	3/8"	5/8"	25	300	19	P-LPL-325-AL	16	2		
P-LP-350-AL	3/8"	5/8"	50	300	27	P-LPL-350-AL	20	3		
P-LP-425-AL	1/2"	3/4"	25	300	29	P-LPL-425-AL	22	4		
P-LP-430-AL	1/2"	3/4"	30	300	31	P-LPL-430-AL	22	4		

COXREELS® Nitro-Pro® Series spring driven hose reels are the only nitrogen hose reels specifically engineered, tested and approved for use with nitrogen tire inflation systems. These professional-grade specialty reels feature compact space-saving size and heavy duty construction for flexible installation and long-lasting performance. The EZ-Coil® model features Coxreels® patented rewind safety system that retracts up to 80% slower than conventional spring driven reels. This reel is specifically designed to reduce workplace accidents and increase operator safety.

### NITRO-PRO® SERIES


HOSE						LESS HOSE		SIZE	
MODEL	I.D.	0.D.	FT.	PSI	APRX. LBS.	MODELS	MODEL	APRX. LBS.	INDEX
P-NP-350	3/8"	5/8"	50	300	43	EZ-P-NP-350	P-NPL-350	36	3

To order  $\textbf{EZ-Coil}^{\circledcirc}$  equipped models less hose, please add prefix "EZ-'

# **REEL DIMENSIONS** Technical Data Sheets Available On Website

SIZE INDEX	W	Н	L	Х	Υ	M	N	
1	57/8"	147/8"	131/2"	5"	6"	3"	5"	
2	61/2"	147/8"	131/2"	5"	6"	3"	5"	
3	63/4"	185⁄8"	171/8"	6"	6"	4"	5"	
4	7"	185/8"	171/8"	6"	6"	4"	5"	
	(	Overall Dimensions	3	Ba Ba	se —	Mounting Pattern —		









# NITRU-PRU® & ALUMI-PRO® SERIES:: REEL SPECIFICATIONS

#### ALUMI-PRO® SWIVEL

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet
- Swivel Seals: NITRILE

#### ALUMI-PRO® DESIGN / STRUCTURE

- Single pedestal reel for applications that require professional grade strength without the weight
- Guide arm adjusts to wall, floor, vehicle & overhead positions
- Industrial strength CPC<sup>™</sup> powder coated aluminum construction
- 1" solid steel axle & lubricated precision bearings for smooth rotation

#### NITRO-PRO® SWIVEL

Nitrogen quality seals in the machined from solid brass 90° full-flow NPT swivel

## NITRO-PRO® DESIGN / STRUCTURE

- Designed for nitrogen tire inflation systems
- Guide arm adjusts to wall, floor, vehicle & overhead positions
- Solid one piece, heavy gauge 1/4" steel base & support post for maximum stability
- Durable special "Nitrogen Green" proprietary CPC™ powder coat finish
- · Green nitrogen hose & hose stop to adjust lead length
- 1" solid steel axle & lubricated precision bearings for smooth rotation

#### *SIGNATURE FEATURES*

- · Professional grade heavy duty steel construction
- Durable proprietary CPC<sup>™</sup> powder coat process
- Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- · Made in the U.S.A. Sold & Supported Worldwide

#### POSSIBLE FIELDS OF APPLICATION

- Nitrogen Dispensing
- Tire Services
- Automotive Dealerships
- Automotive & Fleet Service Centers
- Service / Mechanic Trucks
- Lightweight
- Unit Requirements
- Service / Mechanic Trucks

#### ACCESSORIZE YOUR REEL :: PG 56

- · 0-Rings & Swivels
- Hoses
- Mounting Brackets
- Assorted Reel Accessories



WARNING: Cancer and reproductive Harm – See page 63 for more information – www.P65Warning.ca.gov

