
PURE FLOW SERIES BREATHING AIR & CLEAN FLUID HOS

CLEAN FLUID HOSE REELS



PURE FLOW SERIES :: REEL SPECIFICATIONS

- · Non-corrosive stainless steel air/fluid path with machined from high quality stainless steel 90° full-flow NPT swivel inlet
- Swivel Seals: NITRILE Non-Toxic Food Grade Grease

DESIGN & STRUCTURE

- · Safely store respiratory air hose lines for low or high pressure breathing air systems
- Safely store potable water hose lines for drinking water systems
- Safely store any hose requiring sanitized & non-contaminated fluid transfer application
- Each of these reels is built of their standard series with their own unique features & benefits

- See page 11 for P Series retraction features
- · See page 13 for T Series retraction features
- · See page 40 for 100 Series retraction features
- See page 41 for CM Series retraction features
- · See page 44 for 1125 Series retraction features

SIGNATURE FEATURES

- · Professional grade heavy duty steel construction
- Durable proprietary CPC[™] powder coat process
- · Rolled edges & ribbed discs provide strength & safety
- · Leading 2-year manufacturer's limited warranty
- · Made in the U.S.A. Sold & Supported Worldwide

POSSIBLE FIELDS OF APPLICATION

- · Low Pressure Breathing Air Systems
- · High Pressure Breathing Air Systems
- Fire Rescue
- · Medical & Hospital **Air Services**
- · Mining/Tunneling Operations
- Pharmaceutical Manufacturing
- · Marine/Docks/Offshore
- High Pressure Cylinder Filling (SCUBA/SCBA)

- · Shot Blasting
- Tank Cleaning
- · Spray Painting
- · Hazardous Site Cleanup · Commercial Kitchens
- Pre-Rinse
- · Potable Water
- Bulk Food
- · Food Grade Washdown
- Food & Chemical **Processing Plants**

ACCESSORIZE YOUR REEL :: PG 56

- · 0-Rings & Swivels
- · Mounting Brackets
- Hoses

WARNING: Cancer and reproductive Harm - See page 63 for more information - www.P65Warning.ca.gov

- · Assorted Reel Accessories
- · See page 11 For P Series dim drawing
- · See page 40 For 100 Series dim drawing

COXREELS® Pure Flow Series is offered in spring rewind, hand crank and motorized retractions. All Pure Flow hose reels come standard equipped with stainless steel air/fluid paths and stainless steel swivels with non-toxic, food quality grease, ensuring clean,

non-contaminated, safe and reliable transfer of breathing air, potable water or other clean fluids.

PURE FLOW SPRING DRIVEN SERIES Do not exceed listed hose O.D. to obtain maximum length

MODEL	I.D.	0.D. FT.		PSI	APRX. LBS.	INDEX						
EZ-P SERIES	Models with hose are for air or water service with a maximum temperature 150°F. Models less hose can be used for air, water or oil.											
EZ-P-BLL-350	3/8"	5/8"	50	300	43	1						
EZ-P-BHL-350	Z-P-BHL-350 3/8"		5/8" 50		43	1						
EZ-T SERIES	Models with hose are for air or water service with a maximum temperature 150°F. Models less hose can be used for air, water or oil.											
EZ-TBLL-3100	EZ-TBLL-3100 3/8" 5/8"		100	300	85	2						
EZ-TBHL-3100	3/8"	5/8"	100	6,000	85	2						

Pure flow compact hand crank series

LESS HOSE								
MODEL	I.D.	0.D.	FT.	PSI	APRX. LBS.	INDEX		
100 SERIES								
112P-3-8	3/8"	5/8"	100	4,000	19	3		
CM SERIES								
112P-3-8-CM	3/8"	5/8"	100	4,000	18	3		

PIIRF FI NW HAND CRANK & MOTORITED SFRIFS

LESS HOSE										
MODEL	STA	NDARD	CAP	AP OPTIONAL Reducer rec			INLET SWIVEL & OUTLET	PSI	APRX.	SIZE INDEX
	I.D.	0.D.	FT.	I.D.	0.D.	FT.	RISER		LBS.	
1125 SERIES										
1125P-4-6	1/2"	7/8"	100	3/8"	3/4"	140	1/2" F NPT	6,000	36	4
1125P-4-8	1/2"	7/8"	150	3/8"	3/4"	200	1/2" F NPT	6,000	37	5
1125P-4-12	1/2"	7/8"	200	3/8"	3/4"	300	1/2" F NPT	6,000	39	6

MOTOR OPTIONS When ordering, suffix the model number with selection below. NOTE: Add 5 lbs to ship weight if reel is crated

SUFF	=IX	TYPE	DESCRIPTION	ADD ON APRX. LBS		
Α		AIR - 4 VANE	ALUMINIUM BODY AIR MOTOR	8		
С		FRONT HAND CRANK	BEVEL GEARED CRANK	3		
E		12 V DC, 1/3 HP	REVERSABLE	13		
EA	1	115 V AC, ½ HP EXP.	REVERSABLE AC RECTIFIED	26		
EB	3	24 V DC, 1/2 HP EXP.	EXPLOSION PROOF, REVERSABLE	26		
ED)	12 V DC, 1/2 HP EXP.	EXPLOSION PROOF, REVERSABLE	26		
EF	•	24 V DC, 1/3 HP	REVERSABLE	13		
Н		HYDRAULIC	END PORTED 9/16-18 UNF	6		

REFL DIMENSIONS Technical Data Sheets Available On Website

	W		Н				Υ					
SIZE INDEX	CRANK / ELEC / SPRING	AIR / HYD.	CRANK / SPRING	MOTOR	L	Х	CRANK / SPRING	MOTOR	М	N	Ø	Dw
1	71/8"	-	185⁄8"	-	171/8"	6"	6"	-	4"	5"	11½"	33/4"
2	93/8"	-	251/2"	-	24"	8"	9"	-	7"	8"	153/4"	41/2"
3	18 ¹ /4"	-	13"	-	12"	91/2"	6"	-	5 ¹ /2"	3"	5 ¹ /2"	8"
4	193/4"	17"	185⁄8"	19 ¹ /4"	175/8"	113/8"	15 ³ /8"	16"	9 ⁷ /16"	10"	6 ¹ /4"	6"
5	213/4"	19"	185⁄8"	191/4"	175⁄8"	133/8"	153/8"	16"	117/16"	10"	61/4"	8"
6	253/4"	23"	185/8"	191/4"	175⁄8"	173/8"	153/8"	16"	15 ⁷ /16"	10"	61/4"	12"
		Ovo	rall Dimonei	ono			— Raca —		Mounting	Dottorn	Dri	ım

- · See page 13 For T Series dim drawing
- · See page 41 For CM Series dim drawing
- · See page 44 For 1125 Series dim drawing

