

1/4" - 3/4" I.D.

EZ-T SERIES

SUPREME DUTY HOSE REELS



Triple axle support with a full frame & Super Hub™

COXREELS® EZ-T Series "Truck Mount" spring driven hose reels are the toughest hose reels in the spring driven line. The extra large chassis with dual pedestal-style arms and Coxreels' Super Hub™ provides triple axle support while reducing vibration and strengthening the structural integrity of the reel. This series is ideal for off-road applications that demand reliability in the most abusive and demanding environments.

EZ-T SERIES

Do not exceed listed hose O.D. to obtain maximum length.

HOSE						LESS HOSE		SIZE INDEX
MODEL	I.D.	O.D.	FT.	PSI	APRX. LBS.	MODEL	APRX. LBS.	
LOW PRESSURE Models with hose are for air water service with a maximum temperature 150°F. Models less hose can be used for air, water or oil.								
EZ-TSH-350	3/8"	5/8"	50	300	61	EZ-TSHL-N-350	55	1
EZ-TSH-375	3/8"	5/8"	75	300	82	EZ-TSHL-N-375	73	2
EZ-TSH-3100	3/8"	5/8"	100	300	85	EZ-TSHL-N-3100	74	2
EZ-TSH-450	1/2"	3/4"	50	300	63	EZ-TSHL-N-450	55	1
EZ-TSH-475	1/2"	3/4"	75	300	82	EZ-TSHL-N-475	71	2
EZ-TSH-4100	1/2"	3/4"	100	300	95	EZ-TSHL-N-4100	80	2
EZ-TSH-535	3/4"	1 1/16"	35	300	77	EZ-TSHL-N-535	67	3
EZ-TSH-550	3/4"	1 1/16"	50	300	83	EZ-TSHL-N-550	70	3
MEDIUM PRESSURE Reels are furnished with standard one wire braid hose suitable for air, water or oil applications. Hose exceeds SAE R1 specifications. Maximum Temperature 250°F.								
EZ-TMP-350	3/8"	1 1/16"	50	3,000	74	EZ-TMPL-N-350	61	1
EZ-TMP-375	3/8"	1 1/16"	75	3,000	99	EZ-TMPL-N-375	80	2
EZ-TMP-450	1/2"	1 3/16"	50	2,500	77	EZ-TMPL-N-450	64	1
EZ-TMP-475	1/2"	1 3/16"	75	2,500	100	EZ-TMPL-N-475	80	2
EZ-TMP-550	3/4"	1 1/16"	50	1,500	94	EZ-TMPL-N-550	74	3
HIGH PRESSURE Reels are furnished standard with S.A.E. 100R16 #1 or #2 wire braid hose suitable for grease and hydraulic oil applications. Maximum Temperature 250°F.								
EZ-THP-150	1/4"	9/16"	50	5,000	74	EZ-THPL-N-150	62	1
EZ-THP-175	1/4"	9/16"	75	5,000	88	EZ-THPL-N-175	71	2
EZ-THP-1100	1/4"	9/16"	100	5,000	104	EZ-THPL-N-1100	82	2
EZ-THP-350	3/8"	1 1/16"	50	4,000	78	EZ-THPL-N-350	66	1
EZ-THP-375	3/8"	1 1/16"	75	4,000	98	EZ-THPL-N-375	80	2

EZ-T SERIES :: REEL SPECIFICATIONS

SWIVEL

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Zinc plated steel swivel on HP models)
- Swivel Seals: NITRILE

DESIGN & STRUCTURE

- Sturdy, dual pedestal reel features Coxreels' exclusive Super Hub™ triple axle support system
- Built for rugged mobile applications
- Guide arm adjusts to wall, floor, vehicle, & overhead positions
- Stainless Steel rollers on 3/4" models
- Solid one piece, heavy gauge 1/4" steel base & support posts for maximum strength
- 1" solid steel axle & lubricated precision bearings for smooth rotation

EZ-COIL RETRACTION

- OUR PATENTED SAFETY SYSTEM THAT RETRACTS UP TO 80% SLOWER THAN CONVENTIONAL SPRING DRIVEN REELS
- Enclosed factory tuned & matched cartridge-style spring motor
- Non-corrosive, stainless steel spring, pawl, & zinc plated ratchet
- Multi-position lock ratchet mechanism secures hose at desired length

REEL DIMENSIONS


Technical Data Sheets Available On Website

SIZE INDEX	W	H	L	X	Y	M	N
1	9 3/8"	21 1/4"	19 1/2"	8"	9"	7"	8"
2	9 3/8"	25 1/2"	24"	8"	9"	7"	8"
3	9 7/8"	25 1/2"	24"	8"	9"	7"	8"

Overall Dimensions

Base

Mounting Pattern



TOP REQUESTED UPGRADES & ACCESSORIES

SEE PAGE 17 FOR ADDITIONAL ACCESSORIES

UPGRADE TO NITRILE OR RUBBER HOSE

NITRILE HOSE: Premium high quality, oil resistant, multi-purpose hose. The high tensile spiral synthetic yarn reinforcement provides excellent kink resistance. Temperature range: -20° F to +212° F.

SYNTHETIC RUBBER HOSE: Versatile general purpose hose. The synthetic rubber tube and cover resists heat, sunlight, ozone, and weathering. Temperature range -40° F to +212° F.

UPGRADE TO STAINLESS STEEL SWIVEL

Based on the upgraded medium pressure swivel, the stainless steel swivel is machined from solid 316 stainless steel and features increased wall thicknesses with upgraded seals and backup rings.

UPGRADE TO SOLID ROLLERS

Heavy duty machined from solid plastic rollers. Only for T Series models 3/8" and 1/2".

ADD AIR TOOL KIT

BEND RESTRICTOR: Designed to limit the degree of bending without compromising the integrity of the hose assembly while also preventing the hose-end from kinking, excessive wearing, and tearing. Available for low pressure models.

QUICK DISCONNECT: Quick disconnect couplings tread onto end of hose fitting to provide fast, leak-proof connections for low pressure hose lines.

ADD BEND RESTRICTOR

Designed to limit the degree of bending without compromising the integrity of the hose assembly while also preventing the hose-end from kinking, excessive wearing, and tearing. Available for low pressure models



WARNING: Cancer and reproductive Harm – See page 19 for more information – www.P65Warning.ca.gov

