

# SIDE MOUNT HOSE REELS FOR CABINET MOUNT

# EZ-S SERIES

1/4" - 1/2" I.D.

**COXREELS® EZ-S Series "Side Mount" spring driven hose reels for cabinet mount are compact, versatile, and unique in the way they mount and operate.** They feature a simple two-bolt mounting pattern for easy installation and detachment for multiple workstation applications. EZ-S Series is available for air/water, oil, grease, oxy-acetylene, and T Grade gas welding hose. The 360° hose direction allows the user to operate the reel in any direction the job demands. Common applications include service units, tool benches, tool boxes, vertical walls and beams, vehicle lift systems, machine tools, service vehicles, or any flat vertical surface.



Reel Orientation:  
Right Mount is shown with  
mounting base on the right  
side & hose payout from  
the top of the reel

## EZ-S SERIES

Do not exceed listed hose O.D. to obtain maximum length.


HOSE						LESS HOSE		SIZE INDEX
MODEL	I.D.	O.D.	FT.	PSI	APRX. LBS.	MODEL	APRX. LBS.	
<b>LOW PRESSURE</b>						Models with hose are for air water service with a maximum temperature 150°F. Models less hose can be used for air, water or oil.		
<b>EZ-SR13-L125</b>	1/4"	1/2"	25	300	18	<b>EZ-SR13L-L125</b>	14	<b>1</b>
<b>EZ-SL13-L125</b>	1/4"	1/2"	25	300	18	<b>EZ-SL13L-L125</b>	14	<b>1</b>
<b>EZ-SR15-L135</b>	1/4"	1/2"	35	300	23	<b>EZ-SR15L-L135</b>	17	<b>2</b>
<b>EZ-SL15-L135</b>	1/4"	1/2"	35	300	23	<b>EZ-SL15L-L135</b>	17	<b>2</b>
<b>EZ-SR15-L325</b>	3/8"	5/8"	25	300	23	<b>EZ-SR15L-L325</b>	17	<b>2</b>
<b>EZ-SL15-L325</b>	3/8"	5/8"	25	300	23	<b>EZ-SL15L-L325</b>	17	<b>2</b>
<b>EZ-SR17-L350</b>	3/8"	5/8"	50	300	32	<b>EZ-SR17L-L350</b>	25	<b>3</b>
<b>EZ-SL17-L350</b>	3/8"	5/8"	50	300	32	<b>EZ-SL17L-L350</b>	25	<b>3</b>
<b>EZ-SR17-L430</b>	1/2"	3/4"	30	300	34	<b>EZ-SR17L-L430</b>	29	<b>3</b>
<b>EZ-SL17-L430</b>	1/2"	3/4"	30	300	34	<b>EZ-SL17L-L430</b>	29	<b>3</b>

## REEL DIMENSIONS

Technical Data Sheets Available On Website

SIZE INDEX	W	H	L	Y	M
<b>1</b>	6"	14 1/4"	13"	2 1/2"	9 1/4"
<b>2</b>	6"	16 1/2"	15 1/4"	2 1/2"	10 1/4"
<b>3</b>	5 3/4"	18 1/4"	17"	2 1/2"	13"

Overall Dimensions Base Mounting Pattern



## EZ-S SERIES :: REEL SPECIFICATIONS

### SWIVEL

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet
- Swivel Seals: NITRILE

### DESIGN & STRUCTURE

- Side mount design for vertical flat surface, cabinet, or enclosed space mounts
- 2-bolt mounting pattern easily mounts & detaches for temporary or permanent installation
- Solid, one piece, heavy gauge 1/4" steel arm base for maximum stability
- 1" solid steel axle & lubricated precision bearings for smooth rotation
- Hose control bar prevents hose from slipping off the discs

### EZ-COIL RETRACTION

- OUR PATENTED SAFETY SYSTEM THAT RETRACTS UP TO 80% SLOWER THAN CONVENTIONAL SPRING DRIVEN REELS
- Enclosed factory tuned & matched cartridge-style spring motor
- Non corrosive, stainless steel spring, pawl, & zinc plated ratchet
- Multi-position lock ratchet mechanism secures hose at desired length.
- Non-locking, less ratchet option available (add suffix **-BXC**)

## TOP REQUESTED UPGRADES & ACCESSORIES

SEE PAGE 17 FOR ADDITIONAL ACCESSORIES

### UPGRADE TO NITRILE OR RUBBER HOSE



**NITRILE HOSE:** Premium high quality, oil resistant, multi-purpose hose. The high tensile spiral synthetic yarn reinforcement provides excellent kink resistance. Temperature range: -20° F to +212° F.

**SYNTHETIC RUBBER HOSE:** Versatile general purpose hose. The synthetic rubber tube and cover resists heat, sunlight, ozone, and weathering. Temperature range -40° F to +212° F.



### ADD AIR TOOL KIT

**BEND RESTRICTOR:** Designed to limit the degree of bending without compromising the integrity of the hose assembly while also preventing the hose-end from kinking, excessive wearing, and tearing. Available for low pressure models.

**QUICK DISCONNECT:** Quick disconnect couplings tread onto end of hose fitting to provide fast, leak-proof connections for low pressure hose lines.



### UPGRADE TO STAINLESS STEEL SWIVEL

Based on the upgraded medium pressure swivel, the stainless steel swivel is machined from solid 316 stainless steel and features increased wall thicknesses with upgraded seals and backup rings.



**WARNING:** Cancer and reproductive Harm – See page 19 for more information – [www.P65Warning.ca.gov](http://www.P65Warning.ca.gov)