IN THE EZ-SG & EZ-SGW SERIES SIDE MOUNT HOSE REELS WITH GUIDE ARM



EZ-SG SERIES :: REEL SPECIFICATIONS

SWIVEL


- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Zinc plated steel swivel on HP models)
- Swivel Seals: NITRILE
- External fluid path with 90° full-flow dual ported brass swivel offering both connections from the same side of the reel (On EZ-SGW Models)
- Swivel Seals: VITON® (On EZ-SGW Models)

DESIGN & STRUCTURE

- Side mount design for vertical flat surface, cabinet, or enclosed space mounts
- Adjustable, six position guide arm & roller assembly provide maximum hose control
- 2-bolt mounting pattern easily mounts & detaches for temporary or permanent installation
- Solid, one piece, 3/16" steel arm base for maximum stability
- 1" solid steel axle & lubricated precision bearings for smooth rotation

EZ-COIL RETRACTION

- OUR PATENTED SAFETY SYSTEM THAT RETRACTS UP TO 80% SLOWER THAN CONVENTIONAL SPRING DRIVEN REELS
- Enclosed factory tuned & matched cartridge-style spring motor
- Non corrosive, stainless steel spring, pawl, & zinc plated ratchet
- Multi-position lock ratchet mechanism secures hose at desired length.
- \bullet Non-locking, less ratchet option available (add suffix -BXC)



TOP REQUESTED UPGRADES & ACCESSORIES



UPGRADE'TO SOLID'ROLLERS

Heavy duty machined from solid plastic rollers. Only for T Series models 3/8" and 1/2".



WARNING: Cancer and reproductive Harm – See page 19 for more information – www.P65Warning.ca.gov

COXREELS[®] EZ-SG & EZ-SGW Series expand the capabilities of the "Side Mount" spring driven hose reels, adding a multi-position guide arm for maximum and convenient hose control. Ideal for tight spaces, the versatile EZ-SG Series (for air/water, oil and grease) and EZ-SGW Series (for oxy-acetylene and T Grade gas welding hose) features a simple two-bolt mounting pattern for easy installation and detachment on any vertical flat surface. Common applications include service vehicles, tool benches, vertical walls and beams, vehicle lift systems, machine tools, and many more. The guide arm and roller assembly are easily moved to one of the six different positions with a standard ½" wrench.

EZ-SG SERIES

						exceed listed hose O.D. to obtain maximum length.		
HOSE					LESS HOSE		SIZE	
MODEL	I.D.	0.D.	FT.	PSI	APRX. LBS.	MODEL	APRX. LBS.	INDEX
LOW PRESSURE Models with hose are for air water service with a maximum temperature 150°F. Models less hose can be used for air, water or oil								
EZ-SG13-L125	1⁄4"	1/2"	25	300	25	EZ-SG13L-L125	22	1
EZ-SG13-L135	1/4"	1/2"	35	300	26	EZ-SG13L-L135	23	1
EZ-SG13-L325	3⁄8"	5⁄8"	25	300	26	EZ-SG13L-L325	23	2
EZ-SG17-L350	3⁄8"	5⁄8"	50	300	40	EZ-SG17L-L350	33	3
EZ-SG17-L430	1/2"	3/4"	30	300	42	EZ-SG17L-L430	37	3
EZ-SG19-L450	1/2"	3⁄4"	50	300	52	EZ-SG19L-L450	44	5
MEDIUM PRESSURE						e suitable for air, water or oil ap berature 250°F.	plications.	
EZ-SG17-M325	3⁄8"	¹¹ ⁄16"	25	3,000	46	EZ-SG17L-M325	39	3
EZ-SG19-M350	3⁄8"	¹¹ ⁄16"	50	3,000	63	EZ-SG19L-M350	51	5
EZ-SG17-M425	1/2"	13⁄16"	25	2,500	46	EZ-SG17L-M425	39	4
EZ-SG19-M450	1⁄2"	13⁄16"	50	2,500	65	EZ-SG19L-M450	51	6
HIGH PRESSURE Reels are furnished standard with S.A.E. 100R16 #1 or #2 wire braid hose suitable for grease and hydraulic oil applications. Maximum Temperature 250°F.								
EZ-SG17-H125	1⁄4"	9⁄16"	25	5,000	45	SG17L-H125	39	4
EZ-SG19-H150	1/4"	9⁄16"	50	5,000	62	SG19L-H150	51	7
EZ-SG17-H325	3⁄8"	11/16"	25	4,000	46	SG17L-H325	39	4
EZ-SG19-H350	3⁄8"	11⁄16"	50	4,000	63	SG19L-H350	51	8

EZ-SGW SERIES Hose

MODEL

	Do not	t exceed listed hose 0.D. to ob	tain maxim	um length.
		LESS HOSE		SI7E
PSI	APRX. LBS	MODEL	APRX.	INDEX

OXYGEN-ACETYLENE	Oxy-Acetylene is twin-siamese type meeting R.M.A. and C.G.A. type V.D. grade R specifications. Use of other types of hose is not recommended.							
EZ-SG17W-150	1⁄4"	50	200	59	EZ-SG17WL-150	47	9	
EZ-SG19W-175	1/4"	75	200	77	EZ-SG19WL-175	60	10	
OTHER FUELS Reels with "T Grade" hoses are used for a wide variety of gases, such as MAPP, propane, natural and fuel.								
EZ-SG17WT-150	1⁄4"	50	200	59	EZ-SG17WTL-150	47	9	
EZ-SG19WT-175	1⁄4"	75	200	77	EZ-SG19WTL-175	60	10	

REEL DIMENSIONS Technical Data Sheets Available On Website

ID

FT.

SIZE INDEX	W	н	L	Y	М
1	61/4"	151/2"	131/2"	21/2"	14"
2	63⁄4"	151/2"	131/2"	21/2"	14"
3	63⁄4"	191/2"	17"	21/2"	18"
4	7 ¹ /4"	19 ¹ /2"	17"	21/2"	18"
5	81/2"	22"	191/2"	27⁄8"	201/2"
6	93⁄8"	22"	191/2"	27⁄8"	201/2"
7	9"	22"	19 ¹ /2"	27⁄8"	20 ¹ /2"
8	91/2"	22"	19 ¹ /2"	27⁄8"	201/2"
9	87/8"	19 ¹ /2"	17"	21/2"	18"
10	10½"	22"	191/2"	21/2"	201/2"
Ľ		Overall Dimensions	Base	Mounting Pattern -	

SEE PAGE 17 FOR ADDITIONAL ACCESSORIES

