# PC<sup>10</sup> SERIES

# **COMPACT POWER CORD REELS**



## **PC**<sup>10</sup> **SERIES**:: **REEL SPECIFICATIONS** UL Listed<sup>†</sup>:: Accessories only

- External heavy gauge CPC™ powder coated steel components cover for simple slip ring routine maintenance
- · Electrical current runs through a 25AMP / 600V rated slip ring
- Include 5' lead cable & grounding plug (except on less cord models)

### DESIGN & STRUCTURE

- Compact & lightweight spring driven cord reel save space & facilitate workplace organization
- CoxComposite™ grommet with continuous radius design that does not pinch or catch the cord during operation
- Solid one piece, 12GA steel base & support post for maximum stability
- 1/2" solid steel axle & lubricated precision bearings for smooth rotation

### RETRACTION

- · Enclosed factory tuned & matched cartridge-style spring motor
- Non-corrosive CoxComposite™ ratchet hub with self lubricating bronze bearings secures cord at desired length

## SIGNATURE FEATURES

- · Professional grade heavy duty steel construction
- Durable proprietary CPC<sup>™</sup> powder coat process
- · Rolled edges & ribbed discs provide strength & safety
- · Leading 2-year manufacturer's limited warranty
- · Made in the U.S.A. Sold & Supported Worldwide

## **POSSIBLE FIELDS OF APPLICATION**

- · Power Tools
- · Light Source
- · General Industrial
- · Bench Mount
- · Manufacturing Plants & Facilities
- Workshops
- Automotive & Fleet **Service Centers**
- · Service / Mechanic / **Utility Vehicles**

**COXREELS®** PC<sup>10</sup> Series Power-Cord Series is a unique compact addition to our original line of power cord and light reels. This ground-breaking design sets a new bar as the ideal cord management solution capable of fulfilling any commercial or industrial application where space is limited. Modeled after the LG "Little Giant" Series, this Series is equipped with a continuous radius grommet style power cord guide and a unique C-PEP™ Composite hub featuring excellent chemical resistance and additional strength at cold temperatures.

# PC 10 SERIES

CORD										
MODEL	ACCESSORY	AWG / NO COND.	CORD FT.	TYPE	VOLTS	AMPS	APRX. LBS.	SIZE		
FOR INDOOR USE ONLY! All models rated at 115 volts, 60 hz single phase only.										
PC10-3016-A	Single Industrial Receptacle <sup>†</sup>	16/3	30	SJ0	115	13	14	1		
PC10-3012-A		12 / 3	30	SJ0	115	20	17	1		
PC10-3012-B	Quad "4 Plug" Industrial Receptacle†	12 / 3	30	SJ0	115	20	18	1		
PC10-3016-C	Fluorescent Tube Light - Shock Absorbing & Shatter Resistant	16 / 3	30	SJT0	115	0.3	15	1		
PC10-3016-D	Fluorescent Angle Light with Tool Tap Plug <sup>†</sup>	16 / 3	30	SJT0	115	13	16	1		
PC10-3016-E	Incandescent Caged Drop Light with Tool Tap Plug <sup>†</sup>	16 / 3	30	SJT0	115	13	14	1		
PC10-3016-F	Duplex G.F.C.I. Metal Industrial Receptacle <sup>†</sup>	16 / 3	30	SJ0	115	13	16	1		
PC10-3012-F	-	12/3	30	SJ0	115	20	19	1		
PC10-3016-X	With Cord, Less Accessory	16 / 3	30	SJ0	300	13	14	1		
PC10-3012-X	V	12/3	30	SJ0	300	20	18	1		
PC10L-3016	Less Cord, Less Accessory	16/3	30*	SJ0	300	13	11	1		
PC10L-3012		12/3	30*	SJ0	300	20	11	1		
*Consult factory with 4 conductor requirements.										

**REEL DIMENSIONS** Technical Data Sheets Available On Website

SIZE INDEX	W	н	L	X	Υ	M	N	
1	73/8"	105⁄8"	101/2"	45/8"	83/8"	21/2"	6"	
		Juarall Dimoneione		P2	20	Mounting Pattern		







