






MOUNTING & ROLLER BRACKETS

| PART NO. | REEL SERIES | | | | | | | |
|---|-------------------------|-------------|---|---|----|----|-----------|------|
| | P | SH, MP & HP | T | C | EN | PC | P-W & SHW | P-WC |
|  Swing Bracket For vertical surface mounting, allows reel to swing 180°. Powder coated crinkle black 1/4" steel. Weight: 5 lbs. | 15720 | • | • | | | • | • | • |
| 15725 | | | | • | • | | | |
|  Swivel Bracket For horizontal surface mounting, ball bearing rotation, allows reel to swivel 345°. Powder coated crinkle black heavy gauge steel. Weight: 6 lbs. NOT FOR USE IN CEILING APPLICATIONS. | 15721 | • | • | • | • | • | • | • |
|  EZ-Up Bracket Reel easily slides in & out for easy overhead mounting. Use as an alternative to the #MR-1. Must be ordered with #15724 for "I" or "H" beam installations. Weight: 6.5 lbs. | 15723 | • | • | | | • | • | • |
|  EZ-Up "I" or "H" Beam Adapter Must be ordered with #15723. Powder coated crinkle black, all steel construction. Weight: 5 lbs. | 15724 | • | • | | | • | • | • |
|  Mounting Bracket For overhead mounting, fits 3" to 8 1/2" flange on "I" or "H" beam. Powder coated crinkle black 3/16" bent steel. Weight: 13 lbs. | MR-1 | • | • | | | • | • | • |
| MRT-1 | | | • | • | | | | |
|  4-Way Roller Bracket Heavy gauge steel, powder coated Coxreels blue (4RB). Available in stainless steel (4RB-SS). Weight: 1 lbs. | 4RB 1/4"-3/4" | • | • | • | • | • | • | • |
| 4RB-SS 1/4"-3/4" | | • | • | • | • | • | • | • |

S SERIES MOUNTING & ROLLER BRACKETS

| PART NO. | S SERIES MODELS | | | |
|--|-----------------|-------------|-------------|-------------|
| | SR13 & SL13 | SR15 & SL15 | SR17 & SL17 | SR19 & SL19 |
|  Dual Side Mount Bracket Heavy gauge steel, powder coated crinkle black. Weight: 5 lbs. | 15726-13 | • | | |
| 15726-15 | | • | | |
| 15726-17 | | | • | |
| 15726-19 | | | | • |
|  Single Side Mount Bracket Heavy gauge steel, powder coated crinkle black. Weight: 2 lbs. | SMB1 | • | • | |
| SMB2 | | | • | |
| SMB3 | | | | • |

INLET HOSE ASSEMBLIES



| PART NO. | FITTINGS | I.D. | LENGTH | PSI |
|-----------------|--|-----------|--------|-------|
| 5150-1.5 | 1/4" Male x Female NPT | 1/4" | 18" | 300 |
| 5153-1.5 | 3/8" Male x Female NPT | 3/8" | 18" | 300 |
| 5154-1.5 | 1/2" Male x Female NPT | 1/2" | 18" | 300 |
| 5155-1.5 | 3/4" Male x Male NPT | 3/4" | 18" | 300 |
| 5224-1.5 | 3/8" Male x Male NPT | 3/8" | 18" | 3,000 |
| 5256-1.5 | 1/2" Male x Male NPT | 1/2" | 18" | 2,500 |
| 5290-1.5 | 3/4" Male x Male NPT | 3/4" | 18" | 1,500 |
| 5304-1.5 | 1/4" Male x Male NPT | 1/4" | 18" | 5,000 |
| 5336-1.5 | 3/8" Male x Male NPT | 3/8" | 18" | 4,000 |
| 15717 | Garden 3/4" NPTM (w/Part #10781) x 3/4" NP | 3/4" | 48" | 300 |
| 5423-1.5 | Twin Grade R 1/8" NPTM x BB 9-16 UNF | 1/4" Twin | 18" | 200 |
| 5424-1.5 | "T" Grade Twin Grade R 1/8" NPTM x BB 9-16 UNF | 1/4" Twin | 18" | 200 |

90° ELBOWS



| PART NO. | FITTING THREAD | I.D. | PSI |
|--------------|----------------------------|------|-------|
| 6088 | Brass LP Male x Female NPT | 1/4" | 300 |
| 208 | Brass LP Male x Female NPT | 3/8" | 300 |
| 222 | Brass LP Male x Female NPT | 1/2" | 300 |
| 385 | Brass LP Male x Female NPT | 3/4" | 300 |
| 500 | Steel MP Male x Female NPT | 3/8" | 3,000 |
| 1671 | Steel MP Male x Female NPT | 1/2" | 3,000 |
| 15014 | Steel MP Male x Female NPT | 3/4" | 1,250 |
| 616 | Steel HP Male x Female NPT | 1/4" | 5,000 |
| 617 | Steel HP Male x Female NPT | 3/8" | 5,000 |

HOSE STOPS & GUARDS



| HOSE STOPS PART NO. | HOSE GUARD PART NO. | HOSE | | CORD | OVERALL |
|------------------------|------------------------|--------|-----------|----------|---------|
| | | I.D. | O.D. | | |
| 131 | 237-1 | 1/4" | 1/2" | 12/3 SJO | 2 1/2" |
| 131-1 | 237-1 | - | - | 16/3 SJO | 2 1/2" |
| 633 | 237-1 | 1/4" | Twin Line | - | 3 1/2" |
| 131-3 | 237-1 | 3/8" | 2 1/32" | 10/3 SO | 2 1/2" |
| 131-4 | 398-1 | 1/2" | 3/4" | - | 2 1/2" |
| 254 | - | 1/2" | 3/4" | - | 3 1/2" |
| 430 | 398-1 | 3/4" | 1" | - | 3 1/2" |
| 20214 | - | 1" | 1 9/16" | - | 5" |
| 20215 | - | 1 1/4" | 1 3/16" | - | 5" |
| 20216 | - | 1 1/2" | 2 1/16" | - | 5" |
| 20217 | - | 2" | 2 9/16" | - | 5" |

BEND RESTRICTORS



| ADD SUFFIX | I.D. | DESCRIPTION | PSI |
|-------------|------|---------------------------|-----|
| -BxB | 1/4" | Black PVC Bend Restrictor | 300 |
| -BxB | 3/8" | Black PVC Bend Restrictor | 300 |
| -BxB | 1/2" | Black PVC Bend Restrictor | 300 |

Designed to limit the degree of bending without compromising the integrity of the hose assembly while also preventing the hose-end from kinking, excessive wear, & tearing.

QUICK DISCONNECTS



| PART NO. | I.D. | DESCRIPTION | CONNECTION | PSI |
|----------------|------|------------------|------------|-----|
| 10759-1 | 1/4" | Quick Disconnect | NPT (F) | 300 |
| 10759-2 | 3/8" | Quick Disconnect | NPT (F) | 300 |

Quick disconnect couplings thread onto end of hose fitting to provide fast, leak-proof connections for low pressure hose lines. Conveniently connect, interchange, & secure pneumatic tools or other spraying devices to any air, water, chemical or other hose lines.