

# EZ-P SERIES

## PERFORMANCE HOSE REELS



**COXREELS® EZ-P Series "Performance" spring driven hose reels have a long history of dependability and hassle free performance.** Their compact space-saving size and heavy duty construction make them highly versatile and virtually indestructible. Time-tested proven components, superior design and craftsmanship have contributed to it's worldwide reputation as the most trusted hose reel.

### APPLICATIONS

- Air/Water Services
- Pneumatic Tools
- Washdown
- Lubrication
- Chemical Fluid Transfer
- General Industrial
- Manufacturing Plants & Facilities
- Maintenance, Repair & Operations
- Automotive & Fleet Service Centers

### EZ-P SERIES :: REEL SPECIFICATIONS

#### SWIVEL

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Zinc plated steel swivel on HP models)
- Swivel Seals: NITRILE

#### DESIGN & STRUCTURE

- Sturdy, single pedestal reel with space saving design facilitates workplace organization
- Guide arm adjusts to wall, floor, vehicle, & overhead positions
- Solid, one piece, heavy gauge 1/4" steel base & support post for maximum stability
- 1" solid steel axle & lubricated precision bearings for smooth rotation

#### EZ-COIL RETRACTION

- **OUR PATENTED SAFETY SYSTEM THAT RETRACTS UP TO 80% SLOWER THAN CONVENTIONAL SPRING DRIVEN REELS**
- Enclosed, factory tuned & matched cartridge-style spring motor
- Non-corrosive, stainless steel spring, pawl, & zinc plated ratchet
- Multi-position lock ratchet mechanism secures hose at desired length

#### SIGNATURE FEATURES

- Professional grade, heavy duty steel construction
- Durable proprietary CPC™ powder coat process
- Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- Made in the U.S.A. - Sold & Supported Worldwide

#### ACCESSORIZE YOUR REEL :: PG 17

- O-Rings & Swivels
- Hoses
- Mounting Brackets
- Assorted Reel Accessories

### EZ-P SERIES

Do not exceed listed hose O.D. to obtain maximum length.

HOSE						LESS HOSE		SIZE INDEX
MODEL	I.D.	O.D.	FT.	PSI	APRX. LBS.	MODEL	APRX. LBS.	
<b>LOW PRESSURE</b> Models with hose are for air water service with a maximum temperature 150°F. Models less hose can be used for air, water or oil.								
<b>EZ-P-LP-125</b>	1/4"	1/2"	25	300	27	<b>EZ-P-LPL-125</b>	24	<b>1</b>
<b>EZ-P-LP-135</b>	1/4"	1/2"	35	300	28	<b>EZ-P-LPL-135</b>	25	<b>1</b>
<b>EZ-P-LP-150</b>	1/4"	1/2"	50	300	40	<b>EZ-P-LPL-150</b>	35	<b>3</b>
<b>EZ-P-LP-325</b>	3/8"	5/8"	25	300	28	<b>EZ-P-LPL-325</b>	25	<b>2</b>
<b>EZ-P-LP-330</b>	3/8"	5/8"	30	300	37	<b>EZ-P-LPL-330</b>	33	<b>3</b>
<b>EZ-P-LP-335</b>	3/8"	5/8"	35	300	38	<b>EZ-P-LPL-335</b>	34	<b>3</b>
<b>EZ-P-LP-350</b>	3/8"	5/8"	50	300	43	<b>EZ-P-LPL-350</b>	36	<b>3</b>
<b>EZ-P-LP-430</b>	1/2"	3/4"	30	300	45	<b>EZ-P-LPL-430</b>	40	<b>4</b>
<b>EZ-P-LP-450</b>	1/2"	3/4"	50	300	48	<b>EZ-P-LPL-450</b>	43	<b>4</b>
<b>MEDIUM PRESSURE</b> Reels are furnished with standard one wire braid hose suitable for air, water or oil applications. Hose exceeds SAE R1 specifications. Maximum Temperature 212°F. (If used with water, synthetic fluids 135°F max.)								
<b>EZ-P-MP-425</b>	1/2"	13/16"	25	2,500	49	<b>EZ-P-MPL-425</b>	42	<b>4</b>
<b>EZ-P-MP-430</b>	1/2"	13/16"	30	2,500	51	<b>EZ-P-MPL-430</b>	43	<b>4</b>
<b>HIGH PRESSURE</b> Reels are furnished standard with S.A.E. 100R16 #1 or #2 wire braid hose suitable for grease and hydraulic oil applications. Maximum Temperature 212°F. (If used with water, synthetic fluids 135°F max.)								
<b>EZ-P-HP-125</b>	1/4"	9/16"	25	5,000	48	<b>EZ-P-HPL-125</b>	42	<b>4</b>
<b>EZ-P-HP-325</b>	3/8"	11/16"	25	4,000	49	<b>EZ-P-HPL-325</b>	42	<b>4</b>

### REEL DIMENSIONS

Technical Data Sheets Available On Website

SIZE INDEX	W	H	L	X	Y	M	N
<b>1</b>	5 7/8"	14 7/8"	13 1/2"	5"	6"	3"	5"
<b>2</b>	6 1/2"	14 7/8"	13 1/2"	5"	6"	3"	5"
<b>3</b>	6 3/4"	18 5/8"	17 1/8"	6"	6"	4"	5"
<b>4</b>	7"	18 5/8"	17 1/8"	6"	6"	4"	5"
Overall Dimensions				Base		Mounting Pattern	

