

1/4" - 3/4" I.D.

EZ-T SERIES

SUPREME DUTY HOSE REELS



Triple axle support with a full frame & Super Hub™

COXREELS® EZ-T Series "Truck Mount" spring driven hose reels are the toughest hose reels in the spring driven line. The extra large chassis with dual pedestal-style arms and Coxreels' Super Hub™ provides triple axle support while reducing vibration and strengthening the structural integrity of the reel. This series is ideal for off-road applications that demand reliability in the most abusive and demanding environments.

APPLICATIONS

- Air/Water Services
- Pneumatic Tools
- Washdown
- Lubrication
- Fuel Delivery
- Chemical Fluid Transfer
- General Industrial
- Manufacturing Plants
- Lube Skids & Trucks
- Service/Mechanic/Utility Vehicles
- Mining, Construction, & Railroad Operations
- Automotive & Fleet Service Centers

EZ-T SERIES :: REEL SPECIFICATIONS

SWIVEL

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Zinc plated steel swivel on HP models)
- Swivel Seals: NITRILE
- Electroless nickel plated steel swivel on 1" models

DESIGN & STRUCTURE

- Sturdy, dual pedestal reel features Coxreels' exclusive Super Hub™ triple axle support system
- Built for rugged mobile applications
- Guide arm adjusts to wall, floor, vehicle, & overhead positions
- Stainless Steel rollers on 3/4" & 1" models
- Solid one piece, heavy gauge 1/4" steel base & support posts for maximum strength
- 1" solid steel axle & lubricated precision bearings for smooth rotation

EZ-COIL RETRACTION

- OUR PATENTED SAFETY SYSTEM THAT RETRACTS UP TO 80% SLOWER THAN CONVENTIONAL SPRING DRIVEN REELS
- Enclosed factory tuned & matched cartridge-style spring motor
- Non-corrosive, stainless steel spring, pawl, & zinc plated ratchet
- Multi-position lock ratchet mechanism secures hose at desired length

SIGNATURE FEATURES

- Professional grade, heavy duty steel construction
- Durable proprietary CPC™ powder coat process
- Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- Made in the U.S.A. - Sold & Supported Worldwide

ACCESSORIZE YOUR REEL :: PG 17

- O-Rings & Swivels
- Hoses
- Mounting Brackets
- Assorted Reel Accessories

EZ-T SERIES

Do not exceed listed hose O.D. to obtain maximum length.

HOSE						LESS HOSE		SIZE INDEX
MODEL	I.D.	O.D.	FT.	PSI	APRX. LBS.	MODEL	APRX. LBS.	
Models with hose are for air water service with a maximum temperature 150°F. Models less hose can be used for air, water or oil.								
LOW PRESSURE								
EZ-TSH-350	3/8"	5/8"	50	300	61	EZ-TSHL-N-350	55	1
EZ-TSH-375	3/8"	5/8"	75	300	82	EZ-TSHL-N-375	73	2
EZ-TSH-3100	3/8"	5/8"	100	300	85	EZ-TSHL-N-3100	74	2
EZ-TSH-450	1/2"	3/4"	50	300	63	EZ-TSHL-N-450	55	1
EZ-TSH-475	1/2"	3/4"	75	300	82	EZ-TSHL-N-475	71	2
EZ-TSH-4100	1/2"	3/4"	100	300	95	EZ-TSHL-N-4100	80	2
EZ-TSH-535	3/4"	1 1/16"	35	300	77	EZ-TSHL-N-535	67	3
EZ-TSH-550	3/4"	1 1/16"	50	300	83	EZ-TSHL-N-550	70	3
MEDIUM PRESSURE								
Reels are furnished with standard one wire braid hose suitable for air, water or oil applications. Hose exceeds SAE R1 specifications. Maximum Temperature 250°F.								
EZ-TMP-350	3/8"	1 1/16"	50	3,000	74	EZ-TMPL-N-350	61	1
EZ-TMP-375	3/8"	1 1/16"	75	3,000	99	EZ-TMPL-N-375	80	2
EZ-TMP-450	1/2"	1 3/16"	50	2,500	77	EZ-TMPL-N-450	64	1
EZ-TMP-475	1/2"	1 3/16"	75	2,500	100	EZ-TMPL-N-475	80	2
EZ-TMP-550	3/4"	1 1/16"	50	1,500	94	EZ-TMPL-N-550	74	3
HIGH PRESSURE								
Reels are furnished standard with S.A.E. 100R16 #1 or #2 wire braid hose suitable for grease and hydraulic oil applications. Maximum Temperature 250°F.								
EZ-THP-150	1/4"	9/16"	50	5,000	74	EZ-THPL-N-150	62	1
EZ-THP-175	1/4"	9/16"	75	5,000	88	EZ-THPL-N-175	71	2
EZ-THP-1100	1/4"	9/16"	100	5,000	104	EZ-THPL-N-1100	82	2
EZ-THP-350	3/8"	1 1/16"	50	4,000	78	EZ-THPL-N-350	66	1
EZ-THP-375	3/8"	1 1/16"	75	4,000	98	EZ-THPL-N-375	80	2

REEL DIMENSIONS

Technical Data Sheets Available On Website

SIZE INDEX	W	H	L	X	Y	M	N
1	9 3/8"	21 1/4"	19 1/2"	8"	9"	7"	8"
2	9 3/8"	25 1/2"	24"	8"	9"	7"	8"
3	9 7/8"	25 1/2"	24"	8"	9"	7"	8"

Overall Dimensions

Base

Mounting Pattern

