

## SIDE MOUNT HOSE REELS FOR CABINET MOUNT

# EZ-S SERIES

1/4" - 1/2" I.D.

**COXREELS® EZ-S Series** "Side Mount" spring driven hose reels for cabinet mount are compact, versatile, and unique in the way they mount and operate. They feature a simple two-bolt mounting pattern for easy installation and detachment for multiple workstation applications. EZ-S Series is available for air/water, oil, grease, oxy-acetylene, and T Grade gas welding hose. The 360° hose direction allows the user to operate the reel in any direction the job demands. Common applications include service units, tool benches, tool boxes, vertical walls and beams, vehicle lift systems, machine tools, service vehicles, or any flat vertical surface.

### APPLICATIONS

- Air/Water Services
- Pneumatic Tools
- Lubrication
- Chemical Fluid Transfer
- Welding Shop
- General Industrial
- Cabinet Mount
- Service / Mechanic / Utility Vehicles
- Construction Sites



Reel Orientation:  
Right Mount is shown with  
mounting base on the right  
side & hose payout from  
the top of the reel

### EZ-S SERIES


Do not exceed listed hose O.D. to obtain maximum length.

HOSE						LESS HOSE		SIZE INDEX
MODEL	I.D.	O.D.	FT.	PSI	APRX. LBS.	MODEL	APRX. LBS.	
LOW PRESSURE		Models with hose are for air water service with a maximum temperature 150°F. Models less hose can be used for air, water or oil.						
EZ-SR13-L125	1/4"	1/2"	25	300	18	EZ-SR13L-L125	14	1
EZ-SL13-L125	1/4"	1/2"	25	300	18	EZ-SL13L-L125	14	1
EZ-SR15-L135	1/4"	1/2"	35	300	23	EZ-SR15L-L135	17	2
EZ-SL15-L135	1/4"	1/2"	35	300	23	EZ-SL15L-L135	17	2
EZ-SR15-L325	3/8"	5/8"	25	300	23	EZ-SR15L-L325	17	2
EZ-SL15-L325	3/8"	5/8"	25	300	23	EZ-SL15L-L325	17	2
EZ-SR17-L350	3/8"	5/8"	50	300	32	EZ-SR17L-L350	25	3
EZ-SL17-L350	3/8"	5/8"	50	300	32	EZ-SL17L-L350	25	3
EZ-SR17-L430	1/2"	3/4"	30	300	34	EZ-SR17L-L430	29	3
EZ-SL17-L430	1/2"	3/4"	30	300	34	EZ-SL17L-L430	29	3

### REEL DIMENSIONS

Technical Data Sheets Available On Website

SIZE INDEX	W	H	L	Y	M
<b>1</b>	6"	14 1/4"	13"	2 1/2"	9 1/4"
<b>2</b>	6"	16 1/2"	15 1/4"	2 1/2"	10 1/4"
<b>3</b>	5 3/4"	18 1/4"	17"	2 1/2"	13"
Overall Dimensions			Base		Mounting Pattern



### EZ-S SERIES :: REEL SPECIFICATIONS

#### SWIVEL

- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet
- Swivel Seals: NITRILE

#### DESIGN & STRUCTURE

- Side mount design for vertical flat surface, cabinet, or enclosed space mounts
- 2-bolt mounting pattern easily mounts & detaches for temporary or permanent installation
- Solid, one piece, heavy gauge 1/4" steel arm base for maximum stability
- 1" solid steel axle & lubricated precision bearings for smooth rotation
- Hose control bar prevents hose from slipping off the discs

#### EZ-COIL RETRACTION

- **OUR PATENTED SAFETY SYSTEM THAT RETRACTS UP TO 80% SLOWER THAN CONVENTIONAL SPRING DRIVEN REELS**
- Enclosed factory tuned & matched cartridge-style spring motor
- Non corrosive, stainless steel spring, pawl, & zinc plated ratchet
- Multi-position lock ratchet mechanism secures hose at desired length.
- Non-locking, less ratchet option available (add suffix **-BXC**)

#### SIGNATURE FEATURES

- Professional grade, heavy duty steel construction
- Durable proprietary CPC™ powder coat process
- Rolled edges & ribbed discs provide strength & safety
- Leading 2-year manufacturer's limited warranty
- Made in the U.S.A. - Sold & Supported Worldwide

#### ACCESSORIZE YOUR REEL :: PG 17

- O-Rings & Swivels
- Hoses
- Assorted Reel Accessories

