

# Sewage & DRAIN

## PROFESSIONAL GRADE FEATURES



**HEAVY DUTY SOLID SPUN DISCS WITH ROLLED EDGES** - not stamped, made with first of its kind CNC robotic spinning cell

**LOW PROFILE RISER & OPEN DRUM SLOT** for smooth, even hose wraps

**EXTERNAL FLUID PATH WITH IN-LINE SWIVELS**, electroless nickel plated steel in a in-line fluid path with full flow design

- Viewable on opposite side

**LONG-HANDLED LOCKING PIN** to secure reel from rotation during transport or storage

**HIGH QUALITY STEEL CONSTRUCTION** with our durable CPC™ powder coated finish

**ONE PIECE ALL CNC ROBOTICALLY WELDED** steel "A" frame construction

The electric version features reliable **CHAIN / SPROCKET** rewind system with **YOUR CHOICE OF MOTOR**



- Option - A  
Air Motor  
4 Gast
- Option - AB  
Air Motor  
6 Gast
- Option - E & EF  
12V & 24V  
Motor
- Option - EA, EB, ED & EJ  
Explosion Proof  
12V, 24V, 115V & 230V
- Option - H  
Hydraulic  
Motor

### POSSIBLE FIELDS OF APPLICATION

- Pressure Washing
- Pipeline Maintenance
- High Volume Delivery
- High Pressure Washdown
- Water Jetting
- Sewer & Drain Cleaning
- Water Blasting



[WWW.COXREELS.COM](http://WWW.COXREELS.COM)  
[INFO@COXREELS.COM](mailto:INFO@COXREELS.COM)

5865 S. ASH AVE  
TEMPE, AZ 85283

800.COX.REEL  
480.820.6396

#COXREELS





## P SERIES



- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Zinc plated steel swivel on HP models)
- Swivel Seals: NITRILE
- Sturdy single pedestal spring driven reel with space saving design facilitates workplace organization

| MODEL    | EZ-Coil® Safety Line | I.D. | FT. | PSI   | APRX. LBS. | W x H x L            |
|----------|----------------------|------|-----|-------|------------|----------------------|
| P-MP-325 | -                    | 3/8" | 25  | 3,000 | 49         | 7 x 18 5/8 x 17 1/8" |
| P-MP-425 | EZ-P-MP-425          | 1/2" | 25  | 2,500 | 49         | 7 x 18 5/8 x 17 1/8" |
| P-HP-125 | EZ-P-HP-125          | 1/4" | 25  | 5,000 | 48         | 7 x 18 5/8 x 17 1/8" |
| P-HP-325 | EZ-P-HP-325          | 3/8" | 25  | 4,000 | 49         | 7 x 18 5/8 x 17 1/8" |

## T SERIES - EQUIPPED WITH SUPER HUB™



- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Nickel plated steel swivel on HP models)
- Swivel Seals: NITRILE
- Sturdy dual pedestal reel features Coxreels' exclusive Super Hub™ dual axle support system



| MODEL      | EZ-Coil® Safety Line | I.D. | FT. | PSI   | APRX. LBS. | W x H x L                |
|------------|----------------------|------|-----|-------|------------|--------------------------|
| TMP-N-350  | EZ-TMP-350           | 3/8" | 50  | 3,000 | 74         | 9 3/8 x 21 1/4 x 19 1/2" |
| TMP-N-3100 | -                    | 3/8" | 100 | 3,000 | 106        | 9 3/8 x 25 1/2 x 24"     |
| TMP-N-450  | EZ-TMP-450           | 1/2" | 50  | 2,500 | 77         | 9 3/8 x 21 1/4 x 19 1/2" |
| TMP-N-4100 | -                    | 1/2" | 100 | 2,500 | 106        | 9 3/8 x 25 1/2 x 24"     |
| THP-N-150  | EZ-THP150            | 1/4" | 50  | 5,000 | 74         | 9 3/8 x 21 1/4 x 19 1/2" |
| THP-N-350  | EZ-THP-350           | 3/8" | 50  | 4,000 | 78         | 9 3/8 x 21 1/4 x 19 1/2" |

## 112Y SERIES



- Professional grade, compact & lightweight hand crank reels to store & maintain hose, cord, cable, wire, rope, tape, chain and
- Open drum design for no hassle hose wrap
- Adjustable tension brake to prevent "free-wheeling" during operation, transport or storage.

| MODEL      | CABLE I.D. |      |      |      | HOSE I.D. |      | APRX. LBS. | W x H x L             |
|------------|------------|------|------|------|-----------|------|------------|-----------------------|
|            | 8/3        | 10/3 | 12/3 | 16/3 | 3/8"      | 1/2" |            |                       |
| 112Y-4     | 40         | 75   | 150  | 300  | 50        | 30   | 10         | 12 1/4 x 13 1/8 x 12" |
| 112Y-8     | 80         | 135  | 300  | -    | 100       | 55   | 14         | 15 3/4 x 13 1/8 x 12" |
| 112Y-12    | 150        | 225  | -    | -    | 150       | 75   | 20         | 20 1/4 x 13 1/8 x 12" |
| 112Y-8-CM  | 80         | 135  | 300  | -    | 100       | 55   | 13         | 16 3/8 x 14 3/4 x 13" |
| 112Y-12-CM | 150        | 225  | -    | -    | 150       | 75   | 19         | 20 7/8 x 14 3/4 x 13" |

## 1125 SERIES



- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet (Nickel plated steel swivel on 1" models)
- Swivel Seals: NITRILE (AFLAS on 1" models)
- Exclusive low profile outlet riser & open drum slot design for flat smooth hose wrap
- All welded steel "A" frame construction for superior reel structure

| MODEL      | MOTOR OPTION                     | I.D. | FT. | PSI   | APRX. LBS. | W x H x L                 |
|------------|----------------------------------|------|-----|-------|------------|---------------------------|
| 1125-4-100 | Electric Motor Options Available | 1/2" | 100 | 3,000 | 36         | 19 1/2 x 18 3/4 x 17 5/8" |
| 1125-4-200 |                                  | 1/2" | 200 | 3,000 | 39         | 25 1/2 x 18 3/4 x 17 5/8" |
| 1125-4-325 |                                  | 1/2" | 325 | 3,000 | 48         | 31 1/2 x 18 3/4 x 17 5/8" |
| 1125-5-100 |                                  | 3/4" | 100 | 3,000 | 42         | 26 3/4 x 18 3/4 x 17 5/8" |
| 1125-5-175 |                                  | 3/4" | 175 | 3,000 | 50         | 32 3/4 x 18 3/4 x 17 5/8" |
| 1125-5-200 |                                  | 3/4" | 200 | 3,000 | 55         | 38 3/4 x 18 3/4 x 17 5/8" |
| 1125-5-250 |                                  | 3/4" | 250 | 3,000 | 59         | 42 3/4 x 18 3/4 x 17 5/8" |
| 1125-6-100 |                                  | 1"   | 100 | 3,000 | 69         | 44 1/2 x 18 1/2 x 17 5/8" |

## HP1125 SERIES



- External fluid path with electroless nickel plated steel 90° full-flow NPT swivel inlet
- Swivel Seals: AFLAS
- Exclusive low profile outlet riser (Zinc plated on 1/2" models) & open drum slot design for flat smooth hose wrap
- All welded steel "A" frame construction for superior reel structure

| MODEL        | MOTOR OPTION                     | I.D. | FT. | HP PSI | APRX. LBS. | W x H x L                 |
|--------------|----------------------------------|------|-----|--------|------------|---------------------------|
| HP1125-4-100 | Electric Motor Options Available | 1/2" | 100 | 5,000  | 36         | 19 1/2 x 18 3/4 x 17 5/8" |
| HP1125-4-200 |                                  | 1/2" | 200 | 5,000  | 39         | 25 1/2 x 18 3/4 x 17 5/8" |
| HP1125-4-325 |                                  | 1/2" | 325 | 5,000  | 48         | 31 1/2 x 18 3/4 x 17 5/8" |
| HP1125-5-100 |                                  | 3/4" | 100 | 5,000  | 42         | 26 3/4 x 18 3/4 x 17 5/8" |
| HP1125-5-175 |                                  | 3/4" | 175 | 5,000  | 50         | 32 3/4 x 18 3/4 x 17 5/8" |
| HP1125-5-200 |                                  | 3/4" | 200 | 5,000  | 55         | 38 3/4 x 18 3/4 x 17 5/8" |
| HP1125-5-250 |                                  | 3/4" | 250 | 5,000  | 59         | 42 3/4 x 18 3/4 x 17 5/8" |

## 1175 SERIES



- External fluid path with machined from solid brass 90° full-flow NPT swivel inlet
- Swivel Seals: AFLAS
- Exclusive low profile outlet riser, open drum slot design for flat smooth hose wrap. All welded steel "A" frame construction for superior reel structure

| MODEL      | MOTOR OPTION                     | I.D. | O.D.    | FT. | PSI   | APRX. LBS. | W x H x L             |
|------------|----------------------------------|------|---------|-----|-------|------------|-----------------------|
| 1175-6-50  | Electric Motor Options Available | 1"   | 1 7/16" | 50  | 3,000 | 67         | 24 1/8 x 26 1/8 x 24" |
| 1175-6-100 |                                  | 1"   | 1 7/16" | 100 | 3,000 | 70         | 28 1/8 x 26 1/8 x 24" |
| 1175-6-150 |                                  | 1"   | 1 7/16" | 150 | 3,000 | 75         | 32 1/8 x 26 1/8 x 24" |
| 1175-6-200 |                                  | 1"   | 1 7/16" | 200 | 3,000 | 83         | 36 5/8 x 26 1/8 x 24" |

## 1185 SERIES



- External fluid path with in-line aluminium straight, full flow NPT swivel inlet
- Swivel Seals: NITRILE
- Exclusive low profile outlet riser, open drum slot design for flat smooth hose wrap. All welded steel "A" frame construction for superior reel structure

| MODEL     | MOTOR OPTION                     | I.D.   | O.D.    | FT. | PSI | APRX. LBS. | W x H x L         |
|-----------|----------------------------------|--------|---------|-----|-----|------------|-------------------|
| 1185-1124 | Electric Motor Options Available | 1 1/2" | 2 1/16" | 50  | 600 | 76         | 25 x 26 x 24"     |
| 1185-1524 |                                  | 1 1/2" | 2 1/16" | 75  | 600 | 81         | 29 x 26 x 24"     |
| 1185-2024 |                                  | 1 1/2" | 2 1/16" | 100 | 600 | 94         | 33 1/2 x 26 x 24" |
| 1185-2528 |                                  | 1 1/2" | 2 1/16" | 150 | 600 | 122        | 38 1/2 x 30 x 28" |

## HIGH PRESSURE 1185 SERIES



- External fluid path with electroless nickel plated steel 90° full-flow NPT swivel inlet
- Swivel Seals: AFLAS
- Exclusive low profile outlet riser, open drum slot design for flat smooth hose wrap. All welded steel "A" frame construction for superior reel structure

| MODEL          | MOTOR OPTION                     | I.D.   | O.D.    | FT. | PSI   | APRX. LBS. | W x H x L         |
|----------------|----------------------------------|--------|---------|-----|-------|------------|-------------------|
| 1185-1124-BUXX | Electric Motor Options Available | 1 1/2" | 2 1/16" | 50  | 3,000 | 76         | 25 x 26 x 24"     |
| 1185-1524-BUXX |                                  | 1 1/2" | 2 1/16" | 75  | 3,000 | 81         | 29 x 26 x 24"     |
| 1185-2024-BUXX |                                  | 1 1/2" | 2 1/16" | 100 | 3,000 | 94         | 33 1/2 x 26 x 24" |
| 1185-2528-BUXX |                                  | 1 1/2" | 2 1/16" | 150 | 3,000 | 122        | 38 1/2 x 30 x 28" |

This selection only represents a sample of products applicable in this industry. Please visit us online or consult the factory for more product options.

### CHOICE OF MOTORS



CF-SD-001

